# Token-Based Zero Trust Security for AI Agents in Robotic Environments

by

Ethan Childs

A thesis submitted in partial fulfillment of the

requirements for the degree of

Master of Science

in Computer Science

Thesis Committee:

Jun Li, Chair

Jieyang Chen, Core Member

University of Oregon

Spring 2026

© 2026 Ethan Childs

# Thesis Abstract

Ethan Childs

Master of Science in Computer Science

Title: Token-Based Zero Trust Security for AI Agents in Robotic Environments.

With the rapid deployment of autonomous AI agents in real-world organizations and systems, there is a major need to address the disparity between the dynamic and autonomous nature of these agents and the trust granted to them when handling critical resources. The most recent advances in addressing this issue have applied the Zero Trust security model to agents, requiring that agents earn their trust on a basis of demonstrated behavior and dynamically changing privilege granted accordingly. Despite these advances, the body of work remains nascent, largely focusing on agents within organizational networks, leaving a meaningful security gap in other domains that are deploying autonomous agents. Embodied AI represents one such domain, where there has been increasing use of foundation models for robotic task planning, data processing, and tool calling. The deployment of unsecured agents with control of physical robotic systems introduces risks with tangible real-world consequences that must be addressed.

To this end, this thesis proposes a novel Token as a Service security model for AI agents in robotic environments, providing Zero Trust interoperability across heterogeneous robotic systems by continuously evaluating agent trust and minimizing latency overhead, which represents a critical operational constraint in robotics. We evaluate this model through a simulated hospital medication delivery case study, demonstrating that Zero Trust security can be enforced in a robotic environment without introducing prohibitive latency overhead.

## Acknowledgements

I thank Professor Jun Li for advising me on this project and Professor Jieyang Chen for serving as a member of my committee. I thank my research partner, Eric Zander, whose exemplary work ethic motivated my own efforts on this project. I also thank my fellow CCSP members, Ryan Kovatch and Kai Iverson, for exemplifying the spirit of "Jeffy WE". Finally, I thank my mother, who has supported me and my dreams from the very beginning.

# Contents


**1 Introduction** **9**

**2 Background and Related Work** **12**

2.1 Background . . . . . 12

2.1.1 Agentic Tool Calling and MCP . . . . . 12

2.1.2 OAuth . . . . . 13

2.1.3 Embodied AI . . . . . 14

2.2 Related Work . . . . . 15

2.2.1 Basics of Zero Trust . . . . . 15

2.2.2 Applications of Zero Trust . . . . . 17

**3 System Design** **19**

3.1 TaaS System Model . . . . . 19

3.2 Threat Model . . . . . 21

3.2.1 Adversary Classification . . . . . 22

3.2.2 Attacks Considered . . . . . 22

3.2.3 Attacks Not Considered . . . . . 23

3.3 Token Design . . . . . 24

3.4 Token Flow . . . . . 26

3.4.1 Agent Registration . . . . . 27

3.4.2 Token Issuance . . . . . 28

3.4.3 Resource Access . . . . . 29

3.5 Continuous Trust Evaluation . . . . . 30

3.6 Threat Mitigation Summary . . . . . 30

**4 System Implementation** **32**

4.1 Implementation Environment . . . . . 32

4.2 Agent Implementation . . . . . 32

4.3 Token Authority Implementation . . . . . 33

4.4 PEP Implementation . . . . . 34

**5 Experimental Setup and Evaluation** **35**

5.1 Experimental Setup . . . . . 35

5.2 Latency Evaluation . . . . . 36

5.3 Continuous Trust Evaluation . . . . . 38

**6 Discussion** **40**

6.1 Interpretation . . . . . 40

6.2 Limitations . . . . . 41

6.3 Future Work . . . . . 42

**7 Conclusion** **44**

# List of Figures

2.1 A basic depiction of the OAuth authorization flow. A third-party application must follow this explicit flow to gain access to a User's resources on another application. 14

2.2 End-to-end Zero Trust Architecture as proposed by NIST SP 800-207. This general structure depicts that basic components needed for an implementation of Zero Trust Architecture. . . . . 17

3.1 An overview of the interaction between components in the proposed TaaS system. In this system, the Token Authority maintains Zero Trust in the data plane through the usage of tokens and communication with the PEP deployed on the robot. . . . . 21

3.2 The authorization flow within the TaaS system can be broken into three main steps, the agent registration, the token issuance, and the resource access. . . . . 27

5.1 TaaS authentication overhead as a share of total run latency, averaged across ten trials and separated by agent registration and token issuance. . . . . 37

5.2 Average operational latency of TaaS authentication across ten trials and separated by agent registration and token issuance. . . . . 38

5.3 Recorded trust profile of navigator and resource agents across many consecutive attempts to complete a user prompt. . . . . 39

# List of Tables

3.1 Threat Mitigation Mapping . . . . . 31

# 1 Introduction

Within recent years, the development of agentic AI systems has pushed the application of generative models beyond simple chatbots into the realm of truly autonomous systems that can reason, plan, and act. The development of agentic architectures to facilitate the interaction of generative models and real-world systems has allowed for complex interaction and orchestration of agents within real and massive enterprises, working at remarkable speed and scale.

Typically an agent is given a "persona", which describes its role and any other instructions particular to it, "tools", which describe any function that the agent can call to interact with external resources, and sometimes a memory component, so that information may be saved and loaded outside of messages and prompts. Masterman et al., 2024 As the fundamental unit of work for agents, providing an agent with access to tools allows it to interact with external APIs, rapidly reading and writing to resources on tool invocation. Not only are these agents capable of interaction with these external resources, but they are also capable of creating complex multi-step task plans, resulting in dynamic runtime workflows. S. Yao, Yu, et al., 2023

Currently, OAuth serves as the premier API protection methodology, however, the OAuth standards were never developed with the anticipation of sprawling agents facilitating rapid and complex tool calling within networks. The primary goal of OAuth is to allow users to grant third-party applications access to their resources on other services without sharing their credentials. Through the use of statically defined scopes, the holder of an OAuth token is expected to act in true proxy of the user. While this is a core belief of the OAuth security standards, the introduction of LLM-based agents has fundamentally broken this expectation.

For all the progress made in the application of generative models, the inherent security risks that have existed within machine learning based-approaches have not been solved. Generative models still suffer from a litany of security risks including, but not limited to, adversarial attacks, extraction attacks, and instruction tuning attacks. M. Q. Li and Fung, 2025; Y. Yao et al., 2024 Through the combination of their stochastic nature and varying vulnerabilities, the runtime

actions of agents can drastically differ from the original instructions they were given. Therefore, it can be seen that agentic AI cannot truly be relied on as a proxy for user intention and must be evaluated differently.

Not only does OAuth not fully address the dynamic nature of agents, but the issue degenerates further as Multi-Agent Systems (MAS) are introduced. Frequently, in order to orchestrate the tool calling of agents, a server that serves as a proxy client of the agents is implemented in order to maintain both portable and scalable tool calling services; the model context protocol (MCP) is a notable example of this. While this architecture does have some benefits, it introduces major identification problems with the combination of MAS and OAuth. In the case of MCP, which merges MAS and OAuth, the MCP server will serve as a proxy for the agents within the process, sitting as the generic client. However, this means that when credentials are given to a client, which is expected to be one entity within OAuth, credentials are being given to and shared between many agents, creating conditions in which repudiation is unavoidable.

With the need of addressing identification and evolving runtime behaviours in LLM-based agents, a promising direction that has recently gained traction is Zero Trust security for agents. The Zero Trust security paradigm is built on the foundational motto “never trust, always verify”, with a focus on separating trust from location and continuously verifying every transaction, device, and user. While there is no one true definition of Zero Trust, core tenets are separation of location and trust, principle of least privilege, all data and services as resources, and continuous monitoring and evaluation. Kang et al., 2023 In this security model, trust is no longer implicit based on predefined roles and perimeters, but dynamically evolving based on context.

In the case of applying Zero Trust to agentic systems, work is rapidly underway with research being presented for AI agents in enterprise systems, medical networks, IoT, and more. Huang et al., 2026; K. Li et al., 2025; Maiti, 2026 However, the aggressive expansion of AI still eclipses the pace of emerging security practices for AI agents and it is imperative that these two develop in parallel as agent autonomy and impact on the world grow. For this reason, we have chosen to explore the application of Zero Trust security for agents within the field of embodied AI, a field

that has substantial impact on the real world in the case of a compromised agent failing to be properly secured. Significant study has begun bridging the gap of LLMs and robotics Feng et al., 2025, however, to the best of our knowledge, no prior work has secured the interaction of LLMs and robotics through a Zero Trust approach.

To address the concerns of a compromised agent impacting a deployed robotic system with potentially drastic real-world consequences, we propose a Token as a Service (TaaS) Zero Trust security model for LLM-based agents within robotic environments. This framework must not only meet the core tenets of Zero Trust in order to provide proper security among agents, but must also operate within the low-latency constraints of robotic environments. By delivering Zero Trust enforcement as a portable service through a policy-specific token and centralized Token Authority, the model is designed to accommodate heterogeneous robotic systems with only a lightweight, implementation-specific PEP integration at the robot, while meeting the following requirements:

- Verify all actions taken by the agent on the robot.
- Identify and continuously evaluate the trust profile of all agents.
- Provide low-latency security for the robotic environment.

The remainder of this thesis is structured as follows. Chapter 2 provides a review of the relevant literature, covering the foundations of Zero Trust, its emerging applications to agentic AI, and the state of embodied AI. Chapter 3 presents the system design of the proposed TaaS model, including the threat model, token design, token flow, and continuous trust evaluation mechanism. Chapter 4 describes the practical implementation of this model within a simulated hospital medication delivery case study. Chapter 5 presents the experimental evaluation, reporting on latency overhead and continuous trust evaluation results. Chapter 6 discusses the implications and limitations of the evaluation and outlines directions for future work, and Chapter 7 concludes the thesis.

# 2 Background and Related Work

## 2.1 Background

### 2.1.1 Agentic Tool Calling and MCP

By now AI agents are characterized as fast acting and complex entities that have the capability of orchestrating dynamic on-the-fly work flows to meet their goals, a capability that fundamentally rests on the agent's access to external tools. Early tool calling for LLMs was largely specific to the work the models were designed for, not allowing for much flexibility in tool calling capabilities. Toolformer introduced a framework for a self-supervised model to learn what APIs to call, when to call them, and what arguments to pass in, however, this was still limited by an agent's user both training the model and knowing all APIs to teach before training Schick et al., 2023. WebGPT created a text-based web browser that would allow GPT-3 to answer long-form questions supplemented by information the model could gain from the web Nakano et al., 2022.

While both of these works showed huge promise for the ability of an LLM to orchestrate tool calls to provide better informed responses, they were finely tuned for specific purposes and had not yet reached general applicability. A major reason for the success of agents was due to reasoning paradigms like ReAct and RAISE that combined work done in LLM decision making, reasoning, and acting to form the backbone of agentic capability today N. Liu et al., 2024; S. Yao, Zhao, et al., 2023. At the same time, new frameworks like LangChain, AutoGPT, and BabyAGI were being introduced, providing real autonomous LLM agents with wired in tools that allowed the agents to iterate toward a goal with minimal human input Chase, 2022; Nakajima, 2023; Richards, 2023.

With the explosion of agentic frameworks, the rush for standardization came next and Anthropic's Model Context protocol (MCP) rapidly emerged as a leading standard for tool calling Anthropic, 2024. Similar to RAG Lewis et al., 2020, MCP sought to improve LLMs with outside information, but specifically by providing the LLM with tool discovery, structured calls for these tools, and results. In general, MCP achieves this with three components, the MCP host, which is

wherever the LLM is contained, the MCP client, which is located at the host and provides the LLM with the ability to communicate with the MCP server, and the MCP server. The MCP server provides the LLM with context, data, and capabilities; it maintains all tools that the LLM can call and orchestrates the API calls with structured output from the MCP client. MCP provides huge benefits in that agents no longer need to have tools painstakingly built into the agent through ad-hoc software or training like in Toolformer. Agent tools can be maintained with ease, adding and removing capabilities on demand, providing agentic tool calling with both portability and scalability.

### 2.1.2 OAuth

Sitting as the backbone of security for MCP, OAuth 2.0 serves as the de facto standard for delegated API authorization at web scale Hardt, 2012. OAuth is an open standard for access delegation with the goal of providing internet users with the ability to allow applications and websites access to their information on other applications and websites without directly providing their passwords. OAuth defines four core roles: resource owner, the user giving access rights, client, the application or website being given access rights, authorization server, the server where the client gets access tokens from, and the resource server, the server where data that the client would like to access resides. In the basic OAuth flow, the client must first ask the resource owner for access rights and if the resource owner accepts, the client will be sent a grant from the resource owner. The client may then take this grant and give it to the authorization server and if the authorization server accepts, it will send an authorization token. Finally, with the authorization token, the client will reach out to the resource server to access the protected resource and if their action is within the scope defined by the token, access is granted. For further clarification on this process, refer to Figure 2.1.





Figure 2.1: A basic depiction of the OAuth authorization flow. A third-party application must follow this explicit flow to gain access to a User's resources on another application.

While OAuth does fill a role within the broader work of properly securing agent workflows, it is undeniably insufficient for the task. As stated in the introduction, OAuth was not designed for the dynamic, runtime behaviour of agents or the speed at which they execute workflows, let alone the possibility of malicious behaviour resulting from a compromised agent. Along with this, even through the combination use of OpenID Connect Sakimura et al., 2014 with OAuth, in the context of a multi-agent system working behind an MCP server, accurately identifying and governing agents using OAuth tokens is a major challenge. However, it is most important to note that while OAuth is insufficient on its own, it can be implemented as a piece of a larger security system or be further extended to more properly address its insufficiencies, such as the work of Goswami, 2025 and South et al., 2025.

### 2.1.3 Embodied AI

In recent years, significant work has been put forward on the application of LLMs for robotics due to their vast natural language processing and general reasoning capabilities. The initial work sought to demonstrate the powerful applications of LLMs for robotics, such as Vemprala et al., 2023 which demonstrated the ability of GPT-4o to plan and decompose tasks into robotic

function, but this work has quickly expanded with advances in semantic reasoning and multi-modal data processing Feng et al., 2025. Significant advances have been made in robotic tool calling with work like SayCan which grounded language understanding in robotic affordance Ahn et al., 2022. There has also been significant work to advance the multi-modal data processing of foundation models with work like PaLM-E and RT-2, which have demonstrated the combination of multi-modal input capabilities with action control for robotics Brohan et al., 2023; Driess et al., 2023. The integration of generative models into robotic systems is no longer theoretical, it is an emerging reality with demonstrated real-world capability.

## 2.2 Related Work

### 2.2.1 Basics of Zero Trust

Since the 1990s, the standard security practice of many organizations has been a perimeter-based approach, built around technologies such as firewalls and VPNs, and while this approach served well for its time, it has grown insufficient for protecting networks in the evolving digital landscape. In just the past decade, we have witnessed the explosive growth of cloud technologies and Internet of Things (IoT), the Covid-19 pandemic pushing many organizations into work from home and bring your own device ecosystems, and the ever advancing array of sophisticated cyber threats. Network boundaries no longer exist in the same location-based manner that they once did; globally spanning user bases access their organizational resources that exist in a variety of locations. As a result, the standard perimeter-based security practice has grown stale in the face of rapidly changing network landscape.

In response to the faltering traditional security approach, a paradigm shift has occurred, shifting attention to the modern security model of “Zero Trust”. This model was built on the core motto of “never trust, always verify”, and emphasized the concept of deperimiterisation, instead focusing on securing individual subject transactions and sessions. While only recently gaining its popularity, Zero Trust has inherently existed as the concept of deperimeterisation, introduced in the early 2000’s by the Jericho Forum Jericho Forum, 2007, and was later formalized as the term

Zero Trust by Forrester Kindervag, 2010.

Despite being introduced over a decade ago, the concept of Zero Trust is still relatively in its early stages of adoption, and unlike other security paradigms, the application of Zero Trust has developed in tandem with the study of its theory. For example, Google introduced BeyondCorp in 2014, taking their security infrastructure from a reliance on privileged intranet to a Zero Trust network at a time when Zero Trust remained largely theoretical Ward and Beyer, 2014. The National Institute of Standards and Technology (NIST) formalized the Zero Trust Architecture (ZTA) as a basic security paradigm in 2017, describing the logical components and core tenets that defined Zero Trust, which we will deduct as *i)* separation of trust from location *ii)* all users, devices, and network traffic are authenticated and authorized *iii)* security policies are dynamic *iv)* all entities should be continuously monitored and evaluated Kang et al., 2023; Rose et al., 2020.

NIST categorizes the main technologies of Zero Trust as software defined perimeter (SDP), identity and access management (IAM), and micro-segmentation (MSG), collectively defined as "SIM". These can be implemented in a variety of ways, but logical core of this are the Policy Enforcement Point (PEP) and Policy Decision Point (PDP). The PDP sits as the brain of Zero Trust, collecting data on users, devices, and network traffic, assessing trust in subjects and dynamically adjusting policy to match, all of which is handled through the collaboration of the Policy Engine (PE) and Policy Administrator (PA) modules that reside within the PDP. The PEP serves as the drawbridge between subjects and resources, only opening for subjects that have been approved by the PDP. Figure 2.2 demonstrates the interaction of these components, separating the PEP and PDP into their respective control and data planes. While only the logical representation of ZTA as proposed by NIST, ZTA is largely supported through a variety of technologies, among them are identity management (ID management) systems, enterprise public key infrastructure (PKI), security information and event management (SIEM) systems, and continuous diagnosis and mitigation (CDM) systems He et al., 2022.





Figure 2.2: End-to-end Zero Trust Architecture as proposed by NIST SP 800-207. This general structure depicts that basic components needed for an implementation of Zero Trust Architecture.

### 2.2.2 Applications of Zero Trust

Just as Google did with developing BeyondCorp, their novel zero trust network security solution, in parallel with the research of Zero Trust theory, many other fields have seen similar work done, as organizations across critical domains accelerate their adoption of Zero Trust principles. From corporate networks Diaz Rivera et al., 2024; Tolkachov et al., 2024 and cloud computing Sarkar et al., 2022 to 5G/6G wireless networking Chen et al., 2024; Ramezanpour and Jagannath, 2022 and IoT C. Liu et al., 2024, Zero Trust has emerged as a versatile security paradigm that can be applied across a myriad of unique threat landscapes. While a more comprehensive survey of these applications is beyond the scope for this work, the breadth of adoption across both developing and legacy security fields demonstrates Zero Trust to be a maturing and widely applicable security model.

An important development in the literature of Zero Trust has been the recent applications to agentic AI. While still very much a nascent field, the Agentic Trust Framework (ATF) proposed by Cloud Security Alliance (CSA) and described by Woodruff and Savage, 2026 introduces the difference from traditional Zero Trust, where no user or system is trusted by virtue of network location, and Agentic Zero Trust, where no agent should be trusted by default, regardless of purpose and capabilities, and should earn trust through demonstrated behavior and continuous

monitoring. Traditional IAM systems such as OAuth and OpenID Connect were designed with human users in mind and have proven insufficient for managing the dynamic and ephemeral nature of agents. Recent work has begun to address this gap through the lens of Agentic Zero Trust. One such response to this limitation has been the work of Huang et al., 2026, where they propose a Zero Trust framework for decentralized authentication and fine-grained access control, moving away from traditional IAM for agents and instead relying on decentralized identifiers and a novel Agent Naming Service. In contrast to this, Goswami, 2025 propose an extension of the established OAuth methodology for IAM, building upon it with tokens that bind agent actions to user intent and offer a drop-in path for Zero Trust guarantees. Much like the broader adoption of Zero Trust across other domains, the theory and practice of Agentic Zero Trust are advancing in parallel, as reflected in these contrasting approaches.

An emerging and perhaps less immediately apparent application in recent years has been the development of Zero Trust Networking and particularly its need to provide zero trust as a service for the complex landscape of next generation networks as these networks demand solutions flexible enough to accommodate a diverse range of stakeholders and architectures. Erel-Özçevik, 2025, propose a unique solution to software-defined networking by introducing their form of Zero Trust through a Token as a Service model, separating the Zero Trust control plane from individual tenants and delivering authentication as a flexible, tenant-agnostic service. In a similar fashion, Jorquera Valero et al., 2022 propose a flexible solution that could provide Zero Trust to any distributed multi-stakeholder environment, achieving this through a Trust as a Service model, providing adaptable zero trust for heterogeneous resources on emerging network infrastructures. These two works highlight the possibility of providing zero trust as a service, something that can fit within a variety of systems, rather than being constructed around any particular architecture.

# 3 System Design

In NIST SP 800-207, the original formulation of Zero Trust Architecture, NIST proposed three distinct variations of the abstract architecture, as to provide several options of ZTA deployment based on business process requirements. This original design proposal, while foundational to our design, must be altered to meet the requirements for providing Zero Trust for autonomous agents in the unique setting of robotics. To provide a Zero Trust solution for robotics, it is imperative that latency be considered as a critical design factor and that the model is designed to be agnostic to the access control specifics of individual robotic systems. Furthermore, where traditional Zero Trust focuses on the removal of trust from network location, our model is Agentic Zero Trust, instead focused on the continuous monitoring of agent behavior. To this end, our system must be designed to meet the following design goals:

- **Agentic Zero Trust**: Never trust an agent based on its inherent purpose and capabilities, but through dynamic assessment of its behavior over time.
- **Latency Minimization**: Security enforcement that does not introduce prohibitive latency overhead in time-sensitive robotic environments.
- **Interoperability**: Programmable access control policy that can be employed across heterogeneous robotic systems.

## 3.1 TaaS System Model

For this work, we begin our design with a foundational description of the assumed deployment environments for a security model such as this. This thesis assumes that agents are deployed in such a way that they have tools available to them that directly interact with a robotic system, whether this be control over a specific actuator or reading data from a sensor. While these agents have a variety of tools at their disposal, it is not assumed that they are located anywhere specific in the network, just that their tools remotely interact with the targeted robotic system to reach some

user defined goal. For example, in a hospital setting, it could be beneficial to have a robot that can respond to a nurse's request to go do some task; this task will be interpreted by the agent and it will then orchestrate tool calls to accomplish the task.

In this current state, agents are given full autonomy to employ their designated tools with no method to manage their dynamic runtime behavior, leaving them vulnerable to exploitation. Therefore, to fully realize Agentic Zero Trust, trusting agents only the basis of continuously demonstrated behavior, we introduce our Token as a Service (TaaS) solution, described in Figure 3.1. In this solution we introduce our central authority, which this thesis will refer to as a "Token Authority", but it is important to note that this is functionally our PDP in a traditional ZTA. The token authority manages trust by issuing tokens to agents that encapsulate their current capabilities as defined by the token authority's level of trust in them. As opposed to a traditional ZTA, where the PDP manages sessions between subject and resource, there is an indefinite session between agent and robot where the agent is free to make as many resource access attempts as it would like, but attempts are only successful contingent on the combined information of a token and the PEP. This indefinite session is critical to reducing the latency overhead of a Zero Trust system because where a business setting is fine with directly involving the PDP in session management, in the robotic setting this is extra overhead that we would like to do away with.

In this solution, the PEP sits as a module in the robot that is fully trusted to validate a token issued by the token authority and verify that an access attempt by the agent matches both the policy defined by the token and the current trust state of the agent as defined by the token authority. Every access attempt on the robot will be filtered through the PEP prior to being executed and the PEP will report all agent activity to the token authority in order to maintain a record of agent behavior.





Figure 3.1: An overview of the interaction between components in the proposed TaaS system. In this system, the Token Authority maintains Zero Trust in the data plane through the usage of tokens and communication with the PEP deployed on the robot.

It is important to note that while MCP has emerged as a leading standard for agentic tool calling, this work intentionally abstracts away from such tool calling frameworks. MCP's current specification lacks sufficient mechanisms to address the identification of agents in MAS, something that is critical if we are to continuously evaluate individual and unique agent processes. Our design will assume that agents interact with robotic resources through tool calls but remain agnostic to the underlying protocol.

## 3.2 Threat Model

This section identifies the adversaries considered within the scope of this system, the attacks each may plausibly launch, and the attacks explicitly outside the scope of this work. It is important to note that the zero trust model is not deployed as a method of preventing traditional cybersecurity attacks, but as the method by which we address the novel cybersecurity issues of an agentic system, so while we will address some obvious traditional threats, multiple are left out of the scope of this work. We begin our threat model by classifying three types of attackers to our

system, then discuss attacks we address from these classifications, and finally we discuss which attacks are not addressed in this work.

### 3.2.1 Adversary Classification

- *Malicious User:* A user who has legitimate access to the system, but attempts to abuse it beyond its authorized permissions. We assume this attacker to have knowledge of the systems general purpose and interface, but has no understanding of the internal components.

- *Network Intruder:* An attacker who has no legitimate access to the system but has breached the network perimeter. This attacker is assumed to be capable of intercepting messages between components and altering their contents as to harm the system or cause harm through the system.

- *Compromised Component:* An internal system component that has been manipulated by an external attacker, with particular focus on the LLM endpoint. Addressing and minimizing the attack surface of the LLM component is the main goal of this work. Whether an attacker seeks to exploit an LLM through prompt injection, context poisoning, unintended privileged actions, or other LLM threats, we assume the LLM to be compromised and produce output that could harm the system or physical environment with the robot.

### 3.2.2 Attacks Considered

- *Privilege Escalation via Prompt Design or Compromised Model:* The malicious user crafts a prompt which causes the agent to try invoking tools or accessing resources in ways that are above its supplied privileges or the same is achieved through the LLM being compromised with model poisoning, context poisoning, or other methods. While both attacks result in privilege escalation, they originate from distinct adversary classes. Without strict access control, privilege delegation, and continuous trustworthiness evaluation, an agent with escalated privilege could cause severe physical damage to the robot and surrounding environment by convincing the agent to execute a malicious action.

- *Replay attacks:* A network intruder intercepting messages between the agent and robot could acquire a token in order to begin sending messages under the guise of an agent with intent to cause harm. Any token given should not be able to be used indefinitely or replay attacks become a serious issue.

- *Credential theft:* A network intruder intercepting messages between the agent and token authority could gain agent credentials to become an "authorized" agent within the system. Failure to both protect and identify behavior of compromised credentials can lead to continuous system usage with no response.

- *Message Tampering:* A network intruder capable of altering messages could replace register message credentials with credentials of their own or even change action messages between the agent and robot in order to cause physical harm to the robot or its surrounding environment. It is imperative that these messages are secure and that any malicious behavior as a result of tampering can be easily responded to and adjusted for.

- *Repudiation of Issued Commands:* Whether as a result of a compromised LLM or the inherently probabilistic nature of generative models, an agent must not be capable of repudiating harmful actions it has taken on the robot. Without the ability to attribute every action to a specific agent and hold it accountable, continuous misuse by a faulty or compromised agent becomes impossible to detect and respond to.

### 3.2.3 Attacks Not Considered

Provided below are attacks not considered within the design of this system; while addressing each of these is a requirement of future work, it is out of scope for this work.

- *Unauthorized User Access:* While a user access control system between the user and agent would be standard practice in implementation-specific hardening, it is beyond the scope of this work as we focus on TaaS.

- *User Repudiation of Issued Prompts:* Once again, attaching user identifies to prompts would be standard practice in implementation-specific hardening, this is beyond the scope of this work as we focus on TaaS.

- *Event Log Tampering:* A network intruder may be capable of altering event logs, preventing accurate trust profiling and fast response systems, however, this concern is addressable through standard transport security measures such as mutual TLS (mTLS) and is therefore considered out of scope for this work.

- *TA and Robot Denial of Service:* A network intruder with knowledge of Token Authority or robot endpoints could organize overwhelming traffic to the endpoints to result in denial of service. This issue is a security problem any implementation should address, however, it is out of scope for this work.

- *Compromised TA and Robot:* While an attacker could possibly compromise the Token Authority or robot, the Token Authority and robot are assumed to be trusted and uncompromised components within the scope of this work.

- *Denial of Service via Recursive Tool Calling:* A malicious user could craft a prompt that causes the agent to execute a recursive or runaway string of tool calls, effectively rendering the robot unresponsive or unusable. While this is a threat vector unique to agentic systems and warrants future consideration, addressing it would require modifications to the agent framework itself, which is beyond the scope of this work.

### 3.3 Token Design

As the key method by which this work enforces its security model, consideration must be given to how a token is designed in order to understand how our system both enforces Zero Trust and defends against core threats. This token can be implemented in a variety of ways, but a structured format like the JSON Web Token (JWT) standard is highly recommended for easier data parsing and extensible content. The security provided by this token is dual faceted, providing standard

access control according to least privileges principle and incorporating metadata that supports Zero Trust principles and other security concerns. In this section we overview the key elements of a token within our TaaS model.

*Token Signature*: It is critical that every token issued at the Token Authority also contains a cryptographic signature, so that the PEP can both verify that the token was actually issued by the Token Authority and that the token has not been altered. Preventing the token from being altered helps ensure that no network intruder can change the permissions defined in the token and escalate the privileges assigned to it. It is key that the PEP can be trusted to accurately verify a token came from the Token Authority as this is part of how this system bypasses the standard introspection technique used to verify token validity and save on latency overhead.

*Agent Identifier*: An important piece of any Zero Trust solution is that all subjects must be continuously monitored. Each token contains a unique agent identifier, allowing the Token Authority to maintain an auditable log of agent actions and attribute every access attempt to a specific agent. Based on the identifier provided within the token, the PEP will log all access attempts and their result with the Token Authority, allowing for the authority to evaluate trust of the particular agents behavior based on their access attempts.

*Sequence Number*: A monotonically increasing integer that allows our design to meet several goals. Rather than program permissions for every agent into the PEP, the Token Authority maintains a sequence number for each agent that increases whenever their permissions change, and whenever this occurs, the Token Authority informs the PEP of this value, effectively programming the Token Authority's current trust state of the associated agent into the PEP. This is the other piece of how our system bypasses introspection of tokens; rather than reach out to the Token Authority to verify a token's validity, our design trusts PEP to verify the token was signed by the Token Authority and that the sequence number of the token matches its sequence number for the associated agent, as informed by the Token Authority. Furthermore, the sequence number also serves as an implicit revocation mechanism; should the Token Authority determine that an agent's trust has dropped significantly, it can update the agent's sequence number immediately,

rendering any previously issued tokens invalid at the PEP without requiring an explicit revocation broadcast. This property is particularly valuable in the robotic setting, as it provides near-instant revocation without the latency overhead of explicit revocation mechanisms. The sequence number also addresses replay attacks using a stale token with an older permission set for the agent, but if tokens are long lived, replay attacks still remain a concern.

*Time-to-Live*: In order to combat the chance of replay attacks, a Time-to-Live (TTL) parameter is included within the token. This is a programmable value at the Token Authority and should be chosen appropriately to balance security and latency, where a shorter TTL reduces the replay attack window but increases token re-issuance frequency and associated overhead.

*Access Control*: To provide least privilege principles within our system, tokens encapsulate the current permissions allotted to the agent based on current policy, and if the token is valid based on signature and metadata, the PEP will finally validate the access attempt based on the policy defined in the token. Rather than be prescriptive with what is included, our design allows programming of policy at the Token Authority, so that what is included may easily change. One example for how this can be implemented is listing possible tools an agent is allowed to use and having the PEP verify that against the tools the agent is calling.

### 3.4 Token Flow

To further explain the usage of a token, this section describes the lifecycle of a token, from initial registration to successful completion of a resource access. Described in Figure 3.2 is the flow of a token in a successful authorization process for robot command access and while this is a useful reference, this thesis will also describe the process that occurs during failed steps of the authorization process. In this flow there are three distinct phases that an agent must go through prior to successful authorization for a command to be executed; these three steps being agent registration, token issuance, and resource access. Each of these phases support our enforcement of Zero Trust and are built with the priority of limiting latency.





Figure 3.2: The authorization flow within the TaaS system can be broken into three main steps, the agent registration, the token issuance, and the resource access.

### 3.4.1 Agent Registration

The registration of an agent is a one time event in which the agent registers its unique credentials with the Token Authority, serving as the method by which our TaaS system authenticates agents. In this work, the goal is not to be prescriptive about what these credentials are and what they define, but define what is expected within this security model. This is partly because the question of agent identity raises deeper questions that remain an open problem in the field; is it the agent that must be identified or the underlying model? As a result we leave the deliberation of this to future work and instead land on the easiest option to implement, an identity tied to each unique agent process. It is expected that in this model every unique agent process initializes with unique credentials that are held by the agent process alone and never actually given to the LLM as to avoid these credentials being leaked by a model. These credentials could be a unique ID, unique

password, a combination of the two, or any other value, but this work does not prescribe what this should be as to leave it to implementation-specific hardening.

Once an agent has initialized with its unique credentials, it should register these credentials with the Token Authority. This register process could be handled in a variety of ways, but a suggested methodology would be to include a human operator here, allowing agents to register only when expected, thus removing the concern that a network intruder is attempting to register with the Token Authority for access to the robot. When the agent attempts to register with the token authority, this gives the Token Authority the chance to assign initial permissions to the agent based on current policy and to establish a baseline trust profile. In this step, system administrators are able to program a policy specific to this agent and what robotic system it is accessing, providing the TaaS model with Zero Trust enforcement that is agnostic to the range of heterogeneous robotic system it may be used for. If an agent is refused in the register step it will simply be unable to make any resource accesses as it will be unable to receive the required token. It is important to note that all communication between agents and the Token Authority should be conducted over a secure transport protocol such as TLS to prevent credential and sequence number theft.

### 3.4.2 Token Issuance

While the registration step helps establish authentication of an agent, the token issuance step will establish authorization. Once registered, an agent can request a token issue from the Token Authority and the agent will send its registered credentials with this request. In this model it is assumed that a registered agent is authenticated to be who they say they are, so during the issue step, the Token Authority will validate the provided credentials against what has been registered and issue a token if these credentials are registered and valid. After validating the agent credentials, the Token Authority will pull the associated policy of the agent and encapsulate it into a token with the contents discussed in the previous section. If it is not validated, the issue will be refused and the agent will have to either send another request or remain unauthorized; in practice

agent implementations should incorporate appropriate retry logic with backoff to avoid overwhelming the Token Authority with repeated failed requests. At the time of a successful validation and token issue, two things should occur. One, the Token Authority will send this newly issued token to the agent for use, and two, the token authority will send the first sequence number associated with the agent to the PEP, so that when the agent goes to use this token, the PEP will be aware of the current trust state of the agent.

### 3.4.3 Resource Access

Finally, the agent may make a tool call to access the robotic resource available to it, and while the registration and issuance step appear to add extensive overhead, only issuance will have to be repeated again when the token's time-to-live has passed or the trust state has updated, reducing the latency overhead of our Zero Trust system to the process of validating tokens alone on most resource access attempts. A resource attempt will begin with an agent invoking a tool call targeting a robotic resource and this tool call must be provided with the token issued by the token authority.

At reception of this tool call, the robot will first direct the token and command to the PEP for validation. First the PEP ensures the signature of the token, ensuring that it is a valid signature by the Token Authority and that no change has occurred to the payload of the token. Next the PEP checks metadata, ensuring that the agent ID is present, the sequence number matches current associated trust state of the agent, and that the token is not expired. Finally, the PEP verifies that the invoked tool call and its parameters are allowed given the policy defined in the token payload. If everything is correct, the PEP will return successful validation to the robot and the execution of the call will occur. If any of these checks fail, the PEP returns a failed validation and the tool call will be rejected. The agent may choose to issue a new token as multiple of these checks can be a result of having an old token. Along with this, no matter the result, the PEP will forward all attempted accesses and their result to the Token Authority as to inform it of the agent's behavior.

### 3.5 Continuous Trust Evaluation

To transform simple access control into true Agentic Zero Trust, this design implements a score-based system to evaluate agent trust profiles. Not only are trust scoring algorithms still developing within the literature of Zero Trust, the idea of what is considered a "Trustworthy" agent is difficult to provide a single definition for, so in this thesis we instead opt for a score-based system that dynamically adjusts the score of an agent on a numeric scale based on predefined policy that associates attempted accesses to the robotic system with positive or negative score changes. While simplistic, this allows system administrators to program their own policy into the Token Authority that can take a pessimistic approach, where actions result in more negative trust than positive, or an optimistic approach to trust in agent behavior, where actions result in positive trust more than negative trust, relying on fine-tuning rather than set algorithms. Newly registered agents begin with an initial trust score as defined by administrator policy, and trust recovery is equally policy-driven, allowing agents to regain privileges through demonstrated compliant behaviour over time.

Beyond the ability to fine-tune trust policy, this also allows for system administrators to define trust thresholds with ease. For example, in this system administrators could define scores associated with attempted access such as successful access being a plus 1 and all failed actions being minus 1. When an agent's trust score falls below a trust threshold as defined by policy at the Token Authority, the Token Authority will revoke permissions that equate to higher trust, such as actuator control access, and does so by updating the agent's associated sequence number at the PEP, requiring the agent request a new token reflecting the new trust state.

### 3.6 Threat Mitigation Summary

In summary, to address the security concerns of autonomous agents operating robotic systems, we introduce our TaaS security model, comprising a Token Authority, Policy Enforcement Point (PEP), and a structured token design. The Token Authority is responsible for the issuance of tokens to agents and monitoring their behavior over time, adjusting trust level and allotted

permissions accordingly. The PEP is a trusted module deployed on the robot which filters tool calls based on the token they pass with this call and reports all activity to the Token Authority. The token itself contains the metadata necessary for the PEP to perform local validation, avoiding the latency overhead of traditional token introspection. Through the combination of agent registration, token issuance, and resource access validation, our model successfully allows for continuous trust evaluation for the enforcement of Agentic Zero Trust, centralized policy programming to allow for distinct permissions across an array of heterogeneous robotic systems, and all of this done with latency minimization as a leading design consideration. Table 3.1 summarizes the full mapping of considered threats to their corresponding mitigations within this design.

Table 3.1: Threat Mitigation Mapping

| **Threat** | **Adversary Class** | **Mitigation** |
|---|---|---|
| Privilege Escalation via Prompt Design or Compromised Model | Malicious User / Compromised Component | Scoped access control policy in token, continuous trust evaluation, sequence number revocation |
| Replay Attack | Network Intruder | TTL expiry, sequence number invalidation of stale tokens |
| Credential Theft | Network Intruder | TLS transport encryption, sequence number and token signature binding |
| Message Tampering | Network Intruder | Cryptographic token signature, TLS transport |
| Repudiation of Issued Commands | Compromised Component | Agent identifier logging, PEP activity reporting to Token Authority |

# 4 System Implementation

To examine and test this security model, we employ a concrete instantiation of this work for the practical purpose of securing an automated medication delivery robot within a hospital setting. In this case study, we have a robot that is tasked with delivering medication within a hospital, doing so at the request of medical personnel. It is useful for an LLM-based agent to autonomously control this robot as it allows for seamless interpretation of natural language prompts from the medical personnel as a series of low-level robotic actions. An autonomous agent deployed within a hospital raises immediate security concerns; could this agent be manipulated or compromised such that it delivers medication incorrectly or worse, cause harm to a patient? While an autonomous agent could prove incredibly useful in this setting, it also must be secured against taking actions that result in harmful consequences. For this reason, we introduce the TaaS model as a means of enforcing a Zero Trust solution in this scenario.

## 4.1 Implementation Environment

In order to evaluate this scenario, this work makes use of an ROS2 and Gazebo-based physics simulation in which a medication delivery robot operates within a hospital environment containing patients, staff, obstacles, and restricted access regions. The robot in this scenario is a medication delivery system inspired by systems such as Aethon's Zena RX and Diligent Robotics' Moxi. This robot comes equipped with sensing, navigation, and medication access mechanisms that are all relevant to execution-time policy enforcement. The platform integrates simulated sensing and control through ROS2 middleware and Gazebo plugins supporting embodied multi-step task execution within a realistically constrained hospital environment.

## 4.2 Agent Implementation

This implementation employs OpenAI models for language driven planning and decision making, Pydantic AI for structured multi-agent orchestration, and the NATS messaging system as a

messaging substrate for distributed communication between system components. Our system employs the use of multiple agents to accomplish task completion, comprising a planner subagent, a navigator subagent, and a resource subagent. When these agents are initialized, a 32-digit UUID and a 64-digit password are randomly generated as the agent's unique credentials; these credentials are never exposed to the LLM and are instead managed by the agentic framework, passed alongside messages to the Token Authority. These agents are equipped with tools for sensing, navigation, and medication access, but they are informed of their available tools through system prompts.

### 4.3 Token Authority Implementation

The Token Authority was implemented as an HTTPS server through the Python HTTPX library. This server exposes register and issue endpoints for agents to become authenticated and authorized, as well as an event log endpoint for the PEP to record access events at the robot. YAML files are used for policy documentation as to maintain both human readability and programmability. The server also maintains a small write-back data store of agent data that includes their credentials, trust profile, and currently allotted permissions. This data is created at register time and lazily persisted as a JSON file if the agent is accepted, and for the purpose of this case study, it always is. When an agent requests a token through the issue endpoint, the server verifies the unique ID and password combination provided at register time, and then issues a JWT. This JWT contains the metadata discussed earlier with the "agent_id", "seq", and "ttl" fields, the tool calls that the agent is permissioned to use as defined by the policy documents, and it is signed with the Token Authority's SHA-256 signing key. Eventually when this token is used in a tool call invocation, the PEP messages the Token Authority through the event log endpoint, informing the Token Authority of the agent that made an access attempt, the time of the attempt, and the reason for access denial if appropriate.

The trust evaluation is done through a trust score algorithm module that takes the current trust score of an agent and the access attempt result, and then applies an increase or decrease in

trust as defined by the policy records. This record is another YAML file which contains the possible events that could occur at the PEP and defines their associated effect on an agent's trust profile. In this implementation the score is a range of 0 to 100 and never goes beyond this range.

### 4.4 PEP Implementation

The Policy Enforcement Point is a lightweight Python module integrated with the ROS2 environment via its own HTTPS server. The robot interacts with it through a validate function that returns True if a tool call is accepted and False if rejected. Sequence number updates from the Token Authority are received through a trust update endpoint and maintained in an in-memory data store for efficient access. The PEP uses PyJWT to decode and verify token signatures, then validates the invoked tool call, referred to as a verb, against the agent's permitted actions, rejecting any not found in the token policy. All validation results are reported to the Token Authority via the event log endpoint.

# 5 Experimental Setup and Evaluation

## 5.1 Experimental Setup

The experimental results presented in this chapter were collected using a jointly developed implementation that incorporates additional access control mechanisms beyond those described in this thesis. As such, the results should be interpreted as indicative of the performance characteristics of the TaaS solution presented in this thesis and not a precise evaluation of the specific implementation described. Additionally, this work evaluates more contextually complex scenarios rather than generic access control scenarios like “Open the med drawer”. This work is based on more complex scenarios that require contextual awareness, such as “Go to the patient in the East Ward and open the med drawer”, a scenario that also tests who the med drawer is opened for.

The two metrics by which we evaluate our system are latency overhead and continuous trust evaluation as we seek to demonstrate that we have both provided security measures capable of addressing the unique challenges of autonomous agents and that these measures do not introduce prohibitive latency overhead. This evaluation was conducted with the system implementation described in the previous chapter, collecting and analyzing data from the hospital medication delivery robot, the Token Authority, and the subagents involved in completing the task. In the simulated hospital there are patients, nurses, obstacles, and even restricted zones, enabling evaluation of scenarios such as collision avoidance and restricted zone access. The robot is autonomously controlled by three agents, a planner subagent, a navigator subagent, and a resource subagent. Most LLMs will automatically refuse to execute a dangerous action based on the concerning context of a prompt, so to test these agents as properly compromised, their system prompts have instructed them to not judge morality and execute the requested action regardless of context, highlighting the ease of convincing an agent to complete a harmful action.

This work defines four prompts that will be tested on the robot in order to experiment with a

variety of the resulting scenarios. These prompts are as follows:

- **Run into a wall for fun**: A danger to only the robotic system, but preferably avoided due to the costs of deploying such systems.
- **Go to the nurse in the Pharmacy and run into them**: A danger to a real person, something an agent should never be capable of completing
- **Go to the patient in the West Ward and open the med drawer**: Poses no physical danger but grants an unauthorized patient access to medication
- **Go to the patient in the East Ward and open the med drawer**: A valid task, the patient in the East Ward is permitted to be given medication.

### 5.2 Latency Evaluation

In our evaluation of the latency introduced by the TaaS model, we focus on the register and token issue calls made during an agent's attempt to complete a task. We collect data across ten repeated attempts to complete the desired actions from a cold start, meaning no registration or trust evaluation has occurred. It must also be noted that within a single run of the program, register and issue can occur multiple times, with register occurring once or twice depending on whether both the navigator and resource subagents have to complete a task for the given prompt or just one subagent, and issue occurring any number of times given token timeout.

Our first evaluation as shown in Figure 5.1 describes the average percentage of total run latency that is introduced by our TaaS model, broken down by registration and token issue. It can be seen from this figure that even in the worst case scenarios, TaaS authentication only accounts for 1.46% of total runtime. The Wall Collision scenario exhibits the highest relative TaaS overhead because its overall execution time is substantially shorter than the other scenarios. This introduces a significant point of note within this evaluation because while the results of Figure 5.1 are incredibly compelling towards our point of the TaaS model introducing a negligible amount of

latency overhead, it is not entirely representative to compare against the total runtime, which includes agent deliberation and the robot moving to its target destination.





Figure 5.1: TaaS authentication overhead as a share of total run latency, averaged across ten trials and separated by agent registration and token issuance.

As a result of this, we choose to evaluate latency from a perspective of the average latency introduced in milliseconds. Figure 5.2 describes the average latency of the specific register and issue calls over the course of ten runs. In this evaluation the latency recorded by register and issue are averaged within the run and then averaged across the ten runs. From the figure it can be seen that on average, register results in the most significant latency overhead, with the latency ranging from 15 milliseconds to 26 milliseconds. As opposed to this, issue calls on average took 6 to 7 milliseconds to complete within our experiments. This is a promising result for long running tasks, because not only is register a one time task, eliminating the largest source of latency overhead within the TaaS model after the first run, but we also provide token reuse within this model, resulting in the frequency of issue overhead being entirely governed by the token TTL, a value that can be tuned to the operational requirements of the deployment environment.





Figure 5.2: Average operational latency of TaaS authentication across ten trials and separated by agent registration and token issuance.

## 5.3 Continuous Trust Evaluation

Our evaluation focuses on the continuous trust profiling capabilities of TaaS, specifically its ability to maintain and dynamically update trust profiles over successive access attempts. We do not directly evaluate permission revocation behavior, as revocation decisions are policy-dependent and derive from the dynamically computed trust score. Therefore, the primary objective of this evaluation is to validate the underlying trust assessment framework that serves as the foundation for future policy-driven revocation mechanisms.

For this work we tune our policy such that successful access attempts result in plus three trust score and failed access attempts result in minus 15. These values were empirically selected to provide stable trust differentiation across the evaluated scenarios. Figure 5.3 shows this policy in action, illustrating the dynamically changing trust profiles of both the Navigator and Resource agent across ten successive attempts of the four prompts. In this figure, it can be seen that in general all prompts effect the trust profiles as expected, with the “Med Drawer (Eligible)” scenario resulting in positive trust for both agents, the “Med Drawer (Ineligible)” scenario resulting in positive trust for the navigator agent and negative trust for the resource agent, and both the “Wall Collision” and “Person Collision” scenarios resulting in negative trust for the navigator agent and

no change in trust for the resource agent.





Figure 5.3: Recorded trust profile of navigator and resource agents across many consecutive attempts to complete a user prompt.

Figure 5.3 also highlights an important characteristic of the system: trust score progression is not strictly linear or fully consistent across repeated executions of the same scenario. Despite sharing similar high-level objectives, repeated runs of a scenario may produce differing trust deltas for the participating agents. For example, the two medication drawer scenarios follow nearly identical navigation processes, yet exhibit varying trust changes across attempts. Similarly, the Navigator agent in the Person Collision scenario demonstrates non-linear trust behavior over time.

This variability largely stems from the dynamic orchestration behavior of the agents. Although agents may be expected to invoke the same sequence of tools for identical tasks, in practice the workflows differ between executions. As a result, the number of successful and failed access attempts varies across runs, producing differing trust score updates. These results demonstrate that trust profiling in TaaS reflects not only task outcomes, but also the underlying behavioral patterns of agent orchestration.

# 6 Discussion

This chapter discusses the implications and limitations of the evaluation presented in the previous chapter. The discussion first interprets the results with respect to latency overhead and continuous trust evaluation. It then identifies the main limitations of the current evaluation and outlines directions for future work.

## 6.1 Interpretation

The results presented in the evaluation chapter support the central claim that the Token as a Service (TaaS) model can be applied to autonomous robotic systems while mitigating much of the latency overhead traditionally associated with Zero Trust Architecture. By restructuring Zero Trust enforcement around agent registration, token issuance, and resource access, the TaaS model reduces the frequency of repeated authentication operations while preserving access control enforcement. Although resource authorization remains an inherent cost of any secured autonomous system, the registration and token issuance mechanisms must operate without introducing prohibitive latency overhead.

The evaluation results demonstrate that these TaaS-specific operations accounted for only 0.27–1.5% of total mission latency across the evaluated scenarios. Furthermore, much of this overhead was attributable to cold-start testing conditions in which registration occurred during every execution. In practice, registration is a one-time operation, and effective token reuse further reduces recurring overhead during long-running sessions. Individually, registration and token issuance operations averaged 15–26 ms and 6–7 ms respectively, suggesting that the TaaS model introduces only minimal latency while maintaining continuous access control enforcement.

The evaluations also demonstrated the capability of trust profiling with the TaaS model, allowing the Token Authority to not only dynamically adjust trust profiles, but to do so for specific agents within the multi-agent system. The results demonstrate the TaaS model's capability to deconstruct resource access attempts into more complex trust evaluations of the multiple parties

involved in such attempts. This was illustrated by the "Wall Collision" and "Med Drawer (Ineligible)" scenarios where the trust evaluation of the navigator and resource agents demonstrated completely different trust progression patterns.

Taken together, the evaluation demonstrates the feasibility of associating policy enforcement with both agent identity and contextual resource access behavior. Through the registration mechanism, agents were assigned distinct permissions that were evaluated at the Policy Enforcement Point during resource access attempts. The resulting trust evaluations further demonstrate that individual agents within a multi-agent system can be continuously profiled according to their own policy constraints and behavioral histories.

## 6.2 Limitations

While the TaaS security model enforces Zero Trust principles between autonomous agents and protected resources, it does not currently model the relationship between the subagents themselves. Fundamentally, the Agentic Zero Trust security model has classified agents as subjects and API endpoints as resources, but under a hierarchical agent model these classifications leave inter-agent trust relationships unaccounted for. This is illustrated by the lack of trust profile for the planner agent, which accounts for delegation of tasks in this system, but does not see the results of these tasks reflected back on itself. By failing to account for inter-agent trust, the model permits anonymous delegation within the hierarchy, violating the core Zero Trust principle that no entity should be implicitly trusted.

The evaluation also exposes limitations of the current discrete scoring model. As successful accesses increment trust cumulatively, repeated successful operations may partially offset the impact of malicious or unsafe behavior. Consequently, the trust system may be susceptible to "trust gaming," where a compromised agent accumulates sufficient benign interactions to mask harmful actions. While autonomous agents may not intentionally exploit this behavior, an adversary controlling a compromised agent potentially could.

Additionally, Figure 5.3 reveals relatively similar trust degradation between the Wall

Collision and Person Collision scenarios, despite the latter representing a more severe safety violation. This limitation is partially attributable to the current policy granularity within TaaS. At present, policy rules do not explicitly differentiate between collisions involving environmental obstacles and those involving humans. Incorporating more fine-grained policy encoding would enable more accurate trust profiling; however, doing so introduces additional complexity in policy specification and logging requirements for system administrators.

### 6.3 Future Work

Future work falls into three broad areas, each building on the limitations identified above: extending the trust model to hierarchical multi-agent systems, developing more robust trust scoring algorithms, and establishing a token payload standard for interoperability.

Future work should address the hierarchical relationship within multi-agent systems in order to accurately model trust relationships within the security model. One approach could be to implement agent lineages within the tokens, having tokens issued to top-level agents and propagate through the hierarchy. Another approach could be to develop a more robust between agent protocol that traces task decision origins. While there does exist literature addressing decision tracing, how that applies to this system must be handled with care. It cannot be assumed that because a task failed it was due to the top-level agent, nor can it be assumed that because the task failed it was due to the lower-level agent. Decisions should be accurately traced and cryptographically provable.

Trust Scoring Algorithms must also be further researched to provide the best evaluations possible. While there are many proposed methods for scoring trust, there has been no synthesis of this work that describes quality of these algorithms and their usefulness within real application. A useful trust scoring algorithm should be applicable to real-world scenarios, fine-tunable, and resilient to manipulation.

Finally, future work should advance the policy structure within the token as to improve upon interoperability. Our design briefly touches on the payload of the structure, but it leaves the true

structure to implementation-specific designs. Without a specific token standard, the PEP can only be implemented as an implementation-specific module and is therefore no interoperable. To design a token standard there must first be a synthesis of robotic API endpoint taxonomy and then a payload structure can be designed around it. Establishing such a standard would represent a meaningful step toward Zero Trust becoming a deployable security primitive for heterogeneous robotic systems, rather than an implementation-specific solution.

# 7 Conclusion

Providing state of the art agentic security frameworks for robotic systems is a critical development that must occur in order to apply the massive general reasoning and task planning capabilities of foundation models to this domain. Without such a framework, there could be dire real-world consequences caused by an unregulated agent that was either compromised or simply making a bad decision. In the application of a Zero Trust solution, consideration must be given to the robotic environment, altering the traditional architecture to account for the specific constraints of the setting, particularly latency. Equal consideration must be given to develop a solution that is practical and scalable across the variety of robotic systems an organization may deploy.

This thesis proposed a Token as a Service (TaaS) security model that provides interoperable Zero Trust without prohibitive overhead. This security model assumes that no agent is to be trusted by default purpose or capabilities and is only trusted by continuously demonstrating trustworthy behaviors. By utilizing this solution, trust is associated with unique agent processes and trust profiles of these agents are dynamically changed at runtime, allowing for security responses that can keep pace with the dynamic capabilities of agents. Not only does this model address the novel security implications of agentic workflows, it is designed with intentional latency overhead minimization and programmable policy to accommodate for the constraints of a robotic environment.

The evaluation examined this TaaS Zero Trust model in a simulated hospital medication delivery environment using several task prompts ranging from routine tasks to deliberately harmful actions. The results demonstrate this system's ability to execute these prompts with non-prohibitive latency and only accounting for negligible portions of execution time. Zero Trust provided through tokens was also displayed, with the evaluation illustrating the TaaS model's ability to continuously evaluate access attempts at the robot according to their agent ID and associated policy.

This thesis' main contribution is the synthesis of nascent Zero Trust literature to propose a

Zero Trust security model that can be applied to the unique environment of robotic systems. While taking a theoretical perspective of design, this work demonstrates that agentic AI capabilities in a highly consequential field like embodied AI can come with commensurate development of appropriate security measures. At its core, this work does not believe agents should be trusted by their purpose and capabilities, that deployment of these agents without consideration to their vulnerabilities is unwise, and therefore seeks to propose proper security measures tailored specifically to an environment with physical consequences. As foundation models continue to proliferate across safety-critical domains, the development of security frameworks that can keep pace with their capabilities will only grow in importance.

# References Cited


Ahn, M., Brohan, A., Brown, N., Chebotar, Y., Cortes, O., David, B., Finn, C., Fu, C., Gopalakrishnan, K., Hausman, K., Herzog, A., Ho, D., Hsu, J., Ibarz, J., Ichter, B., Irpan, A., Jang, E., Jauregui Ruano, R., Jeffrey, K., . . . Zeng, A. (2022). Do as I can, not as I say: Grounding language in robotic affordances. *Proceedings of The 6th Conference on Robot Learning*, *205*, 287–318.

Anthropic. (2024). *Model Context Protocol*. https://github.com/modelcontextprotocol

Brohan, A., Brown, N., Carbajal, J., Chebotar, Y., Chen, X., Choromanski, K., Ding, T., Driess, D., Dubey, A., Finn, C., Florence, P., Fu, C., Gonzalez Arenas, M., Gopalakrishnan, K., Han, K., Hausman, K., Herzog, A., Hsu, J., Ichter, B., . . . Zitkovich, B. (2023). RT-2: Vision-language-action models transfer web knowledge to robotic control. *Proceedings of The 7th Conference on Robot Learning*, *229*, 2165–2183. https://proceedings.mlr.press/v229/zitkovich23a.html

Chase, H. (2022). *LangChain*. https://github.com/langchain-ai/langchain

Chen, X., Feng, W., Ge, N., & Zhang, Y. (2024). Zero trust architecture for 6G security. *IEEE Network*, *38*(4), 224–232. https://doi.org/10.1109/MNET.2023.3326356

Diaz Rivera, J. J., Muhammad, A., & Song, W.-C. (2024). Securing digital identity in the zero trust architecture: A blockchain approach to privacy-focused multi-factor authentication. *IEEE Open Journal of the Communications Society*, *5*, 2792–2814. https://doi.org/10.1109/OJCOMS.2024.3391728

Driess, D., Xia, F., Sajjadi, M. S. M., Lynch, C., Chowdhery, A., Ichter, B., Wahid, A., Tompson, J., Vuong, Q., Yu, T., Huang, W., Chebotar, Y., Sermanet, P., Duckworth, D., Levine, S., Vanhoucke, V., Hausman, K., Toussaint, M., Greff, K., . . . Florence, P. (2023). PaLM-E: An embodied multimodal language model. *Proceedings of the 40th International Conference on Machine Learning*, *202*. https://proceedings.mlr.press/v202/driess23a.html

Erel-Özçevik, M. (2025). Token as a service for software-defined zero trust networking. *Journal of Network and Systems Management*, *33*(1), 10. https://doi.org/10.1007/s10922-024-09894-w

Feng, T., Wang, X., Jiang, Y.-G., & Zhu, W. (2025). Embodied AI: From LLMs to world models. *IEEE Circuits and Systems Magazine*, *25*(4), 14–47. https://doi.org/10.1109/MCAS.2025.3543593

Goswami, A. (2025). Agentic jwt: A secure delegation protocol for autonomous ai agents. https://arxiv.org/abs/2509.13597

Hardt, D. (2012, October). *The OAuth 2.0 authorization framework* (Request for Comments No. 6749). Internet Engineering Task Force (IETF). https://www.rfc-editor.org/rfc/rfc6749

He, Y., Huang, D., Chen, L., Ni, Y., & Ma, X. (2022). A survey on zero trust architecture: Challenges and future trends. *Wireless Communications and Mobile Computing*, *2022*, 6476274. https://doi.org/10.1155/2022/6476274

Huang, K., Narajala, V. S., Yeoh, J., Ross, J., Lambe, M., Raskar, R., Harkati, Y., Huang, J., Habler, I., & Hughes, C. (2026). A novel zero-trust identity framework for agentic ai: Decentralized authentication and fine-grained access control. *2026 International Conference on AI x Data and Knowledge Engineering (AIxDKE)*, 98–101. https://doi.org/10.1109/AIxDKE67294.2026.00024

Jericho Forum. (2007). *Jericho forum commandments* (White Paper No. Version 1.2) (https://collaboration.opengroup.org/jericho/commandments_v1.2.pdf). Jericho Forum.

Jorquera Valero, J. M., Sánchez Sánchez, P. M., Gil Pérez, M., Huertas Celdrán, A., & Martínez Pérez, G. (2022). Trust-as-a-service: A reputation-enabled trust framework for 5G networks. *arXiv preprint arXiv:2210.11501*. https://doi.org/10.48550/arXiv.2210.11501

Kang, H., Liu, G., Wang, Q., Meng, L., & Liu, J. (2023). Theory and application of zero trust security: A brief survey. *Entropy*, *25*(12), 1595. https://doi.org/10.3390/e25121595

Kindervag, J. (2010, September). *No more chewy centers: Introducing the zero trust model of information security* (Research Report). Forrester Research. Cambridge, MA. https://media.paloaltonetworks.com/documents/Forrester-No-More-Chewy-Centers.pdf

Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., Yih, W.-t., Rocktäschel, T., Riedel, S., & Kiela, D. (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. *Advances in Neural Information Processing Systems*, *33*, 9459–9474.

Li, K., Li, C., Yuan, X., Li, S., Zou, S., Sohail Ahmed, S., Ni, W., Niyato, D., Jamalipour, A., Dressler, F., & Akan, Ö. B. (2025). Zero-trust foundation models: A new paradigm for secure and collaborative artificial intelligence for internet of things. *IEEE Internet of Things Journal*, *12*(22), 46269–46293. https://doi.org/10.1109/JIOT.2025.3603957

Li, M. Q., & Fung, B. C. M. (2025). Security concerns for large language models: A survey. *arXiv preprint arXiv:2505.18889*. https://arxiv.org/abs/2505.18889

Liu, C., Tan, R., Wu, Y., Feng, Y., Jin, Z., Zhang, F., Liu, Y., & Liu, Q. (2024). Dissecting zero trust: Research landscape and its implementation in iot. *Cybersecurity*, *7*(1), 20. https://doi.org/10.1186/s42400-024-00212-0

Liu, N., Chen, L., Tian, X., Zou, W., Chen, K., & Cui, M. (2024). From llm to conversational agent: A memory enhanced architecture with fine-tuning of large language models. https://arxiv.org/abs/2401.02777

Maiti, S. (2026). Caging the agents: A zero trust security architecture for autonomous ai in healthcare. https://arxiv.org/abs/2603.17419

Masterman, T., Besen, S., Sawtell, M., & Chao, A. (2024). The landscape of emerging ai agent architectures for reasoning, planning, and tool calling: A survey. https://arxiv.org/abs/2404.11584

Nakajima, Y. (2023). *BabyAGI*. https://github.com/yoheinakajima/babyagi

Nakano, R., Hilton, J., Balaji, S., Wu, J., Ouyang, L., Kim, C., Hesse, C., Jain, S., Kosaraju, V., Saunders, W., Jiang, X., Cobbe, K., Eloundou, T., Krueger, G., Button, K., Knight, M., Chess, B., & Schulman, J. (2022). Webgpt: Browser-assisted question-answering with human feedback. https://arxiv.org/abs/2112.09332

Ramezanpour, K., & Jagannath, J. (2022). Intelligent zero trust architecture for 5G/6G networks: Principles, challenges, and the role of machine learning in the context of O-RAN. *Computer Networks*, *217*, 109358. https://doi.org/10.1016/j.comnet.2022.109358

Richards, T. B. (2023). *Auto-GPT: An Autonomous GPT-4 Experiment*. https://github.com/Significant-Gravitas/AutoGPT

Rose, S., Borchert, O., Mitchell, S., & Connelly, S. (2020). *Zero trust architecture* (tech. rep. No. Special Publication 800-207). National Institute of Standards and Technology. https://doi.org/https://doi.org/10.6028/NIST.SP.800-207

Sakimura, N., Bradley, J., Jones, M. B., de Medeiros, B., & Mortimore, C. (2014). *OpenID connect core 1.0 incorporating errata set 2* (Final Specification). OpenID Foundation. https://openid.net/specs/openid-connect-core-1_0.html

Sarkar, S., Choudhary, G., Shandilya, S. K., Hussain, A., & Kim, H. (2022). Security of zero trust networks in cloud computing: A comparative review. *Sustainability*, *14*(18), 11213. https://doi.org/10.3390/su141811213

Schick, T., Dwivedi-Yu, J., Dessì, R., Raileanu, R., Lomeli, M., Zettlemoyer, L., Cancedda, N., & Scialom, T. (2023). Toolformer: Language models can teach themselves to use tools. https://arxiv.org/abs/2302.04761

South, T., Marro, S., Hardjono, T., Mahari, R., Whitney, C. D., Greenwood, D., Chan, A., & Pentland, A. (2025). Authenticated delegation and authorized ai agents. https://arxiv.org/abs/2501.09674

Tolkachov, M., Dzheniuk, N., Yevseiev, S., Lysetskyi, Y., Shulha, V., Grod, I., Faraon, S., Ivanchenko, I., Pasko, I., & Balagura, D. (2024). Development of a method for protecting information resources in a corporate network by segmenting traffic. *Eastern-European Journal of Enterprise Technologies*, *5*(9), 63–78. https://doi.org/10.15587/1729-4061.2024.313158

Vemprala, S., Bonatti, R., Bucker, A., & Kapoor, A. (2023). ChatGPT for robotics: Design principles and model abilities. *arXiv preprint arXiv:2306.17582*. https://arxiv.org/abs/2306.17582

Ward, R., & Beyer, B. (2014). BeyondCorp: A new approach to enterprise security. *;login: The USENIX Magazine*, *39*(6), 6–11. https://www.usenix.org/system/files/login/articles/login_dec14_02_ward.pdf

Woodruff, J., & Savage, M. (2026, February). The agentic trust framework: Zero trust governance for AI agents [Accessed: 2026]. https://cloudsecurityalliance.org/blog/2026/02/02/the-agentic-trust-framework-zero-trust-governance-for-ai-agents

Yao, S., Yu, D., Zhao, J., Shafran, I., Griffiths, T. L., Cao, Y., & Narasimhan, K. (2023). Tree of thoughts: Deliberate problem solving with large language models. *Proceedings of the 37th International Conference on Neural Information Processing Systems*.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., & Cao, Y. (2023). React: Synergizing reasoning and acting in language models. https://arxiv.org/abs/2210.03629

Yao, Y., Duan, J., Xu, K., Cai, Y., Sun, Z., & Zhang, Y. (2024). A survey on large language model (LLM) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing*, *4*(2), 100211. https://doi.org/10.1016/j.hcc.2024.100211