

Design Report: Stormwater Improvements

Spring 2020
Silverton

Gary Reyes • Gunter Roehrig • Jacob Ellston
Eric Thomas • Abraham Salazar

Civil & Environmental Engineering Capstone

Spring 2020

Silverton

Design Report: Stormwater Improvements

**Gary Reyes • Gunter Roehrig • Jacob Ellston
Eric Thomas • Abraham Salazar**

Report Authors

Evan Kristof

Senior Instructor • Department of Civil and Environmental Engineering

PORTLAND STATE UNIVERSITY



Acknowledgments

The Capstone team would like to acknowledge the following engineers for their mentorship and expertise.

Shannon Williams, PE, Keller Associates

Scott Nebeker, PE, Oregon

David Seman, Former Engineer, KPFF

Petra Schuetz, City of Silverton Public Works Director

This report was prepared as part of a class project for the Civil and Environmental Engineering Project Management and Design course at Portland State University. Student authors developed the contents of this report; these contents do not necessarily reflect the views of Portland State University. The analyses, conclusions, and recommendations contained in the report should not be construed as an engineering report or used as a substitute for professional engineering services.

Contents

| | |
|----|---|
| 4 | About SCI |
| 4 | About SCYP |
| 5 | About Silverton, Oregon |
| 6 | Executive Summary |
| 7 | 1.0 Project Understanding |
| 9 | 2.0 Alternatives Analysis |
| 15 | 3.0 Facility Design |
| 18 | 4.0 Regulatory Compliance and Permitting |
| 19 | 5.0 Conclusion |
| 20 | References |
| 21 | Appendices |

About SCI

The Sustainable Cities Institute (SCI) is an applied think tank focusing on sustainability and cities through applied research, teaching, and community partnerships. We work across disciplines that match the complexity of cities to address sustainability challenges, from regional planning to building design and from enhancing engagement of diverse communities to understanding the impacts on municipal budgets from disruptive technologies and many issues in between.

SCI focuses on sustainability-based research and teaching opportunities through two primary efforts:

1. Our Sustainable City Year Program (SCYP), a massively scaled university-community partnership program that matches the resources of the University with one Oregon community each year to help advance that community's sustainability goals; and

2. Our Urbanism Next Center, which focuses on how autonomous vehicles, e-commerce, and the sharing economy will impact the form and function of cities.

In all cases, we share our expertise and experiences with scholars, policymakers, community leaders, and project partners. We further extend our impact via an annual Expert-in-Residence Program, SCI China visiting scholars program, study abroad course on redesigning cities for people on bicycle, and through our co-leadership of the Educational Partnerships for Innovation in Communities Network (EPIC-N), which is transferring SCYP to universities and communities across the globe. Our work connects student passion, faculty experience, and community needs to produce innovative, tangible solutions for the creation of a sustainable society.

About SCYP

The Sustainable City Year Program (SCYP) is a year-long partnership between SCI and a partner in Oregon, in which students and faculty in courses from across the university collaborate with a public entity on sustainability and livability projects. SCYP faculty and students work in collaboration with staff from the partner agency through a variety of studio projects and service-

learning courses to provide students with real-world projects to investigate. Students bring energy, enthusiasm, and innovative approaches to difficult, persistent problems. SCYP's primary value derives from collaborations that result in on-the-ground impact and expanded conversations for a community ready to transition to a more sustainable and livable future.

About Silverton, Oregon

The first settlers came to the banks of Silver Creek, following timber and water power, in the 1800s. Silverton was incorporated in 1885. The young town was a trading and banking center of prominence and ranked among the most progressive towns of western Oregon.

By 1921, Silverton industries were producing exports for other areas and even some foreign countries. The Fischer Flour Mills on South Water Street was among the exporters. Power for the mill was obtained by damming Silver Creek at a point near the present pool, diverting water into a millrace that ran along the creek to the mill and then dumped back into the creek.

The development and opening of the Oregon Garden in the 1990s signify the success of a partnership between the Garden, a private enterprise attracting tourists to botanical displays, and the city of Silverton. The Oregon Garden's

expansive wetlands area has benefited from the City's excess reclaimed water since 2000, while the community benefits from trade the Garden draws to the area. Silverton was recognized for these reuse efforts as a "Community Water Champion" by the National Water Reuse Association in 2018.

Today, approximately 10,380 residents call the city of Silverton home. In addition to the Oregon Garden, the City features a historic downtown, hospital, community pool, and access to nature activities including nearby Silver Falls State Park.

Executive Summary

The City of Silverton is a small rural community in Marion County approximately 12 miles northeast of Salem. The City is named after Silver Creek, which runs through town and is the primary feature of the project site radiating from YMCA's Silverton Community Swimming Pool. The City utilizes indigenous water supply to serve community needs, with two intakes in Abiqua Creek and as well as an intake at Silver Creek adjacent to the YMCA Pool. Downtime at this intake must be minimized so as to not compromise the City's water supply if the other intake goes down or if it is needed to fill excess demand. Silver Creek is also critical habitat for steelhead, a native migratory fish, so water quality control must be addressed and National Marine Fisheries guidelines must be considered. The main purpose of intake improvement is to increase pipe capacity 150% from two cubic feet per second (cfs) to five cfs. As the initial leg of pipe from the intake goes under the YMCA Pool parking lot, the City is taking the opportunity to update the pool parking lot up to code for pool use. The scope of the 2020.SILV.01 team's work includes the expansion of this parking lot.

The city of Silverton requires low impact design methods that are economically feasible while mitigating surface runoff and limiting tree removal as much as possible. To minimize costs of the parking lot expansion, the new parking lot design retains the majority of existing asphalt. Working closely with Keller Associates engineer Shannon Williams, the 2020.SILV.01 capstone team designed several iterations of the parking lot to preserve as many trees in the green area surrounding the existing lot as possible while extending the lot to the east and north. The final design indicates two 12-inch diameter ash trees east of the existing lot would be removed to make room for an additional twelve parking spaces, increasing available parking 24% from 44 to 56. An additional eight-inch pine tree would be removed from the northwest corner of the lot to install a rain garden. The rain garden would filtrate water runoff from the lot, which would still primarily be impervious asphalt. To further mitigate environmental impact of the expansion students recommended that the pine and ash trees be replaced with four saplings due to their advanced growth.

Students recommended that the expanded area of the lot to the east be paved with permeable asphalt to improve water filtration. The analysis question for this project was how to pave the extended portion of the lot. Non-permeable asphalt, permeable pavers, and a no-build option were also considered for the additional lot area. Weighing the accessibility, safety, environmental, aesthetic, and economic implications of using each material, including cost and maintenance, students determined that permeable asphalt would be the optimal material for the expansion.

To ensure adequate filtration of lot overflow water, students designed two rain garden areas for the northern side of current. The total area of the proposed dual rain garden areas is 560 square feet, adequately filtering for the 14,000 square feet of impervious pavement at a design infiltration rate of 2.5 inches per hour. Paired with the previous lot pavement, filtration for the expanded lot should be adequate to keep runoff from polluting Silver Creek.

The city of Silverton, Oregon is updating its city parks and recreational facilities as part of their Parks and Recreation Master Plan. The Master Plan incorporates improvements to the YMCA Community Swimming Pool. The improvements include the expansion of the existing parking lot and onsite mitigation of stormwater runoff. The Portland State Capstone team, in collaboration with Keller Associates, developed a design to offer the most suitable solution possible for the city of Silverton and the community center. This report describes the existing conditions, project location, stakeholders, alternative analysis, and selection criteria, determining the best option for the City.

1.0 Project Understanding

The purpose of the Silverton's Parks and Recreation Master Plan is to add value to their greenspaces, parks, and recreational facilities. These resources are essential for maintaining a sense of community, health, and a state of well-being for Silverton's residents.

The City is looking to invest in the swimming pool facility (which is under contract with the YMCA), to enhance community connectivity and services to its residents. The YMCA facility is a popular city attraction year-round. However, the facility sees its peak capacities during the summer months. With the existing parking lot configuration, the facility faces limited capacity to effectively manage all pool-goers during the peak season.

The City is planning a project that will include onsite stormwater runoff mitigation and the expansion of the existing parking lot configuration at the YMCA Pool. The existing parking lot consists of 44 standard parking stalls and three ADA accessible stalls. An existing bike rack with a capacity for seven bikes is located southeast of the main entrance. The current stormwater

system includes a catch basin with an oil filtration system that drains into Silver Creek, located west of the YMCA Pool.

After assessing the current conditions, students pursued an option that will expand the parking lot to the northeast of the lot (currently part of Old Mill Park). Additionally, a more sustainable approach will govern the proposed stormwater runoff mitigation, maintaining a low impact design characteristic.

Completed work to date includes existing condition assessment, low impact design research, and minimal CAD design work to delineate the proposed expansion. The design will follow City of Silverton codes and Design Standards, Americans with Disabilities Act (ADA), and Standard Local Operating Procedures.

1.1 EXISTING SITE CONDITIONS

The YMCA Pool is located southwest of city hall in the heart of downtown Silverton. The existing parking lot conditions consist of 44 standard parking stalls and three ADA-compliant stalls. The existing bike rack has a capacity for seven bikes. The parking lot is graded to drain towards the northwest corner of the lot where the stormwater infrastructure exists. The stormwater infrastructure consists of one catch basin and three manholes that house an oil filtration system, treating runoff before it drains into Silver Creek.




FIG. 1
Aerial of site location
and work area.

1.2 STAKEHOLDERS

The project has several stakeholders with different levels of involvement as described below.

- **City of Silverton:** The City will be funding and taking ownership of the project. Upon completion, the City will provide future maintenance and address questions from the public.
- **Keller Associates:** Keller Associates is the main consulting firm for this project and will be the engineer of record. They will also oversee the project both during the design and construction phases.
- **Homeowners:** During the construction phase, temporary parking lot closures may affect street parking in nearby areas. Furthermore, construction noise in the area may disturb nearby residents.
- **Local Businesses:** During the construction phase, local businesses may experience disturbances due to material deliveries and heavy machinery used during the expansion of the parking lot.

- **Silverton Residents, Pool Users:** The primary goal of the project is to expand the pool's parking lot. During construction, the parking lot will close temporarily. However, the completion of the project will expand the parking lot's capacity and in turn improve vehicle access to the pool. The primary project beneficiaries will be the residents of Silverton and YMCA pool users. The completion of the project will increase water resources for the City while also improving the YMCA facility.

2.0 Alternatives Analysis

Students conducted an alternatives analysis to rate certain criteria for four alternative options concerning the pavement type proposed for the project. The alternatives included no build, non-permeable asphalt, permeable asphalt, and permeable parking stalls incorporated with permeable asphalt. The following sections define each alternative, review the selection criteria, and highlight the final decision.

2.1 CONSIDERED ALTERNATIVES

The considered alternatives are described below.

2.1.1 Alternative 1: No Build

The no build option maintains the existing parking lot configuration. The option mitigates the need for expansion or any additional stormwater improvements.

2.1.2 Alternative 2: Non-Permeable Asphalt

Alternative 2 paves an expanded lot with standard asphalt. Standard pavement is considered a non-permeable surface, which increases the amount of uncaptured/untreated runoff. In this option, runoff would be treated via the existing oil filtration system and new rain gardens incorporated into the parking lot expansion.

2.1.3 Alternative 3: Permeable Asphalt for the Expanded Area

Alternative 3 utilizes an environmentally friendly approach that implements Best Management Practices (BMPs), which would allow the design to be considered a low impact design (LID). The expanded parking area would

be paved with permeable asphalt. Permeable asphalt allows runoff to be infiltrated directly through the pavement and into the soil below, treating water before it reaches the water table. Permeable surfaces minimize pooling that would otherwise be generated by non-porous asphalt in the lot.

2.1.4 Alternative 4: Permeable Paver Stalls and Permeable Asphalt

Alternative 4 is also an environmentally friendly option that allows the design to be considered a LID. The design includes two permeable material types: permeable asphalt and permeable pavers. As described in Alternative 3, permeable asphalt guides runoff into the soil below, allowing water treatment before reaching the water table. In addition to the asphalt, each stall would incorporate permeable paving bricks that also treat runoff while improving visual aesthetics. The pavers require less maintenance than asphalt and can be easily repaired individually.

2.2 SELECTION CRITERIA

This project maintains a variety of design options that will ideally meet Silverton's expectations. Considerations include the parking lot expansion and the effects of increased stormwater runoff created by an increase in impermeable surface area. The team's top priorities were to create an efficient parking design that will increase parking capacity without disrupting traffic flow and mitigate the increased stormwater runoff with sustainable infrastructure. Students developed a list of selection criteria to provide an understanding of how each design will meet the qualifications of these two priorities. The criteria are access, safety, environmental, aesthetics, maintenance, and cost. The following subsections will define each criterion and briefly explain how and why each design option received its score. Each section will receive a score from 1 to 5 and the description of said scores can be found in Table 2.1.

2.2.1 Access

Access considers several different aspects pertaining to the ability of traffic to move through the lot. The first consideration pertains to the ability of personal vehicles to safely and efficiently move through the parking lot. Will these vehicles have ample parking to use during peak pool-going hours? The second consideration pertains to pedestrian and bicycle access. Is the space safe for pedestrians and bicyclists? Do bicyclists have easy access to bike parking? The third consideration pertains to ADA-compliant parking options to accommodate those with disabilities. The final consideration pertains to how well the designs incorporate room for emergency access. Design access will not vary from Alternatives 2 through 4 so it received a weight of 1.

- Alternative 1 (No-Build) received the Lowest accessibility score. This option meets some of the accessibility criteria, however, ADA requirements are not met because there are not a sufficient number of ADA-compliant spaces. Therefore, this option was given a score of 2.
- Alternative 2 (Non-Permeable Asphalt) increases the number of ADA compliant spaces and the number of

general spaces. However, the number of spaces fails to meet standards of the pool at maximum capacity. The possible pooling of water also affects accessibility. Therefore, Alternative 2 was given a score of 3 indicated it is neutral for this category.

- Alternatives 3 (Permeable Asphalt, Expanded Area) and 4 (Permeable Asphalt and Parking Stalls) alleviate the pooling issues but having the same layout that does not satisfy space requirements for pool capacity. Therefore, these options were given a score of 4, meeting most criteria.

2.2.2 Safety

Safety relates to access but holds distinct characteristics and was scored separately. Students considered the vehicle safety in each design including how effectively users can park and maneuver without interfering with each other. Pedestrians and cyclists must also be able to easily navigate the design when entering and exiting the pool facility. Finally, crime must be considered as parking lots can be magnets for a variety of crimes. Safety will be ranked according to the visibility throughout the parking lot and the amount of lighting incorporated in the design. Even though safety is important

when considering the designs, it received a weight of 1 because it does not heavily affect the scope of the project and the safety will not vary from changes of paving material.

- Alternative 1 will add no additional lighting to deter criminal activity, however the basic layout of the current parking lot is such that drivers can maneuver within the lot reasonably safely. Alternative 2 adds additional lighting to deter crime. However, the possibility of ponding due to differential settlements decreases safety. Alternatives 1 and 2 were given a score of 3.
- Alternatives 3 and 4 reduce the possibility of ponding and were given a safety score of 4, meeting most requirements but not getting a score of 5 as 1-way lanes limit maneuverability.

2.2.3 Environmental

The environmental criterion examines how well the design's ability to mitigate stormwater runoff. The increase in the impermeable surface area poses a risk to overwhelm the current runoff management system. The design should consider green water infrastructure options that not only capture runoff but help infiltrate and treat runoff. Ultimately this criterion was based on how effectively the design captures and treats water to reduce its impact on Silver Creek. Environmental aspects were a main focus when deciding between design options as students believe this parking lot expansion is an opportunity to create better stormwater management. The environmental criterion received a weight of 2.5.

- Alternative 1 receives an environmental score of 2, having some environmental management features that could be better managed. The new parking lot layout adds rain gardens to improve stormwater management and planting strips to support wildlife.
- Alternative 2 utilizes these features, however its non-permeable pavement is poorer environmentally relative to other alternatives. Therefore, this option was determined to be neutral with a score of 3.
- Permeable pavement options have the lowest environmental impact, thus Alternatives 3 and 4 received a score of 5.

2.2.4 Aesthetics

Students considered aesthetics when grading the designs. Since the site will be heavily used by the community, students sought an attractive design that can be enjoyed by the users. This grade was based purely on the visual appeal of each design. Students gave this criterion a weight of 1 because it is not of major importance to the design function.

- Alternative 1 scored the lowest with a score of 2. The current site is not visually appealing and when compared to the enhanced features of other options it is aesthetically lacking.
- Alternatives 2 and 3 both received a score of 4. Both designs will look relatively the same as there is not a large difference in looks between porous and non-porous asphalt.
- Alternative 4 scored the highest with a score of 5 as the addition of pavers enhances the visual appeal of a parking lot by incorporating designs similar to brick.

2.2.5 Maintenance

Maintenance is a frequently overlooked design aspect. Students envisioned a design that requires very little maintenance for both short- and long-term scenarios. When deciding on a score, students considered the following categories. First, the roadway surface should require very little cleaning and should not be subject to unconventional failures leading to potholing. Next, the green infrastructure should be free of maintenance outside of the normal cleaning that is required. Lastly, students considered the additional maintenance that could be added from the incorporation of new plants, trees, and landscaping. Maintenance received a weight of 1.5 as the variability of required upkeep changes immensely in each design.

- For Alternative 1 students scored Maintenance as a 3. The current site is showing signs of deterioration, suggesting increases in required maintenance are necessary to maintain the integrity of the driving surface.
- Alternative 2 scored the highest with a score of 4, as the non-porous pavement requires less cleaning and the new pavement should have increased integrity.
- Alternative 3 received a score of 1, as the porous pavement requires increased cleaning to maintain its ability to infiltrate and treat runoff. It is also subject to an increased failure rate from moving vehicles.
- Alternative 4 received a score of 2 as it still requires increased cleaning frequency, but the incorporation of pavers increases the lifespan of the stalls and if needed can be replaced individually instead of across whole sections.

2.2.6 Cost

Cost is an important factor when considering designs as ambitious designs often increase costs considerably. To score Cost, students examined several factors, the first being the cost of labor. Cost of labor includes the overall length of construction and amount of work required by the contractor. Secondly, design feasibility must be factored in as it must be deemed possible for a contractor to efficiently complete the scope of work. Lastly, material cost needs to be considered as increased design complexity can often increase overall material costs. Therefore, the cost was an overall driving factor in this project receiving a weight of 3.

- Alternative 1 received a score of 5 as it would require no additional costs to leave the site as-is. For the remaining three alternatives students only compared the difference in the pavement as the overall layout would not be changed and would not affect the cost between the three.
- Alternative 2 received a score of 4. This option required basic asphalt paving, which is the most cost-effective of the three pavement options for both material and labor costs. The alternative is also considered feasible.
- Alternative 3 acquired the score of 3 as both material and labor costs would increase slightly while remaining feasible.
- Alternative 4 received a score of 2. Both the material and labor costs will rise significantly from the addition of porous pavers. This alternative was also considered slightly less feasible than other alternatives.

2.2.7 Pugh Matrix

The following tables define the meaning of each score (1-5) and illustrate how students' overall design choice was derived. Students selected the design alternative with the highest tallied score as the best fit design for the project. As described above, the team scored the

criteria for each alternative. After the criteria were scored, all of the scores were totaled. The highest scoring alternative was Alternative 3, permeable asphalt for the entire lot (Table 2.2). Since Alternative 3 had the highest rank, it was deemed to be the preferred alternative.

| Score | Description |
|-------|--|
| 1 | Does not meet the criteria description |
| 2 | Barely meets the criteria description |
| 3 | Neutral (meets some but not all) |
| 4 | Meets most of the criteria description |
| 5 | Meets the entire criteria description |

TABLE 2.1
Description of Scoring

| Criteria | Weight | Design Alternatives | | | | | | | | | |
|---------------|--------|----------------------------|----------|--|----------|---|----------|---|----------|--------------------------|--|
| | | Alternative 1: No-Build | | Alternative 2: Non-Permeable Asphalt | | Alternative 3: Permeable Asphalt for Expanded Area | | Alternative 4: Permeable Paver Stalls and Permeable Asphalt | | Preferred Alternative | |
| | | Score | Weighted | Score | Weighted | Score | Weighted | Score | Weighted | | |
| Access | 1 | 2 | 2 | 3 | 3 | 4 | 4 | 4 | 4 | 3 & 4 | |
| Safety | 1 | 2 | 2 | 3 | 3 | 4 | 4 | 4 | 4 | 3 & 4 | |
| Environmental | 2.5 | 2 | 5 | 3 | 7.5 | 5 | 12.5 | 5 | 12.5 | 3 & 4 | |
| Aesthetics | 1 | 2 | 2 | 4 | 4 | 4 | 4 | 5 | 5 | 4 | |
| Maintenance | 1.5 | 3 | 4.5 | 3 | 4.5 | 1 | 1.5 | 2 | 3 | 1 & 2 | |
| Cost | 3 | 5 | 15 | 4 | 12 | 3 | 9 | 2 | 6 | 1 | |
| | | | | | | | | | | | |
| Total | | 16 | 30.5 | 20 | 34 | 21 | 35 | 22 | 34.5 | 3 | |
| Final Rank | | 4 | | 3 | | 1 | | 2 | | | |

TABLE 2.2
Scores of each design alternatives

3.0 Facility Design

The following section will discuss the final design proposal that will be submitted. It is organized into the following sections: overall design, mitigation of increased runoff, mitigation of current run, and additional issues that arose.

3.1 DESIGN CRITERIA

The design criteria for the parking lot expansion considers the implementation of BMPs, ADA, and city of Silverton requirements. Incorporating innovative stormwater management into the parking lot design requires using “best management practices” or LID.

3.2 EXPANSION OF PARKING LOT

To address the lack of current parking spaces in the lot, students propose to expand the current design to the east. The proposed design includes a one lane route that will add an additional 11 spaces to the parking lot while maintaining the majority of the existing spaces (Appendix D, 6). Additionally, the current travel directions will change from two-way to one-way with the exception of the main entrance. Overall, the new design will be about 18,530 SF and will total of 56 parking spaces.

3.3 MITIGATION OF INCREASED RUNOFF

As discussed in the prior section, the parking lot will have an increased area of about 4,530 square feet (SF). The increase leads to additional stormwater runoff that needs to be managed in an effective manner. Student alternatives analysis considered several options including porous pavement, porous pavement with permeable pavers, and impermeable asphalt. Ultimately, Alternative 3 was chosen, which included the incorporation of porous asphalt in the expanded section.

To ensure the porous pavement can manage the increased runoff, students used HydroCAD to produce a runoff analysis. Students designed the porous asphalt with no underdrain as the detailed geotechnical report provided by GeoEngineers found that soil on the site has an infiltration rate of 0.5 inches per hour (in/hr). The storm was modeled as a 10yr Type IA 24-hr storm, which represents storms of low intensity but long duration, a common occurrence in the Pacific Northwest. Finally, students adjusted the time frame to 30 hours to adhere to the performance approach listed in the City of Portland’s Stormwater Management Manual.

Overall, students concluded that the porous pavement could effectively manage the increased runoff based on the analysis. By examining the hydrograph, the peak runoff is 0.05 CFS and the overall flow returns to zero within the 30-hour time frame, proving the design will handle the runoff (Appendix E, 13-18).

3.4 MITIGATION OF CURRENT RUNOFF

Two parking sections were designed for this project. One is the additional parking area proposed that will use porous asphalt on the east side of the existing impervious asphalt.

For the impervious asphalt, there is approximately 14,000 SF calculated for the analysis. To treat the runoff for this section, students proposed two planters to mitigate the water runoff.

These planters would be located on the north side of the lot (Appendix D, 7). The Presumptive Approach Calculator (PAC) was used to estimate the size of the planter needed to mitigate the runoff. A geotechnical report from GeoEngineers specifically for this site showed that the soil has an infiltration rate of 0.5 in/hr. This value was used for calculations as well as the Open Pit Falling Head method with a 10-year storm requirement.

The final proposed size for the planter is 560 SF. This area was distributed in two planter facilities. The resulting size for the planter located on the NE corner of the lot is about 7' by 27' and next to it, another planter with dimensions of 7' by 53' (Appendix D, 7). A hierarchy category 3 and facility configuration C were chosen for maximum efficiency. The calculations performed suggested a 543 SF planter. However, the actual size of the two planters combined is greater than the minimum required area by the PAC method, which makes the design capable of infiltrating the estimated runoff (Appendix E, 2).

3.5 ADDITIONAL PROBLEMS THAT AROSE

Within the parking lot design process, an additional complication arose that required the team to complete electronic turning templates to analyze the existing and proposed conditions of the parking lot configuration and traffic flow. The electronic turning templates are CAD-based and illustrate or simulate vehicular paths that include starting, turning, and ending maneuvers of a vehicle. They are used to verify that access to and from the parking lot will not generate any complications. Students generated electronic turning diagrams for two types of vehicles (in accordance with AASHTO 2018 vehicle library dimensions) that

include passenger and emergency vehicles. These are the main two types of vehicles that the parking lot configuration needs to accommodate (Appendix D, 9-10).

3.6 CONSTRUCTION COST

The construction costs for the project are relatively preliminary and will need further work as the project develops. There are many different types of costs associated with the project, including labor, equipment, demolition, installation, materials, and temporary signage and barricades among others. Labor costs include work done by all the contractors throughout the construction of the project. Equipment costs include drilling vehicles for site investigation, pavers for the asphalt, and compact excavators for the removal of curb, earth, and light poles. Newly installed items for the project include six new light poles, approximately 4,530 SF of porous pavement, and a rain garden for all runoff collected from the existing pavement. Material costs include asphalt, concrete, light poles, subgrade, and PVC pipe. Other costs include temporary signage and barricades to help keep the public safe distance. A detailed list showing each item and its cost can be found in Appendix A (1-3).

3.7 CONSTRUCTION SCHEDULE

The construction schedule for the YMCA Pool parking lot will occur in four phases with a pre-construction phase zero.

- Phase 0 includes pre-construction activities such as design, planning, design approval, contract execution, and phase review. Phase 0 assumes that a team working on this type of

design may take about 12 days to produce a design.

- Phase 1 is the period of construction. The first task is equipment mobilization followed by demolition of the area where the new design will be implemented. Site grading will provide the necessary slope for water runoff to be captured by the planter on the north side and by the porous asphalt in the new east area. Piping will facilitate stormwater management following the details provided in Appendix D for the planter. In this phase, any utility such as gas or electric conduit must be securely moved if necessary. The east side of the parking lot has a tree that must be removed for the expansion to take place. On the north side, the vegetated area will be reduced to about 8' by 16'; design efforts were taken to conserve existing trees in this area.
- In Phase 2, all concrete work for the curb, planter, and light pole

foundations is scheduled to be completed in approximately six days. The details for these three items are given in Appendix D. Additionally, ground preparation is scheduled in this phase, where a geosynthetic layer will be placed above soil followed by coarse aggregate and lastly by porous asphalt.

- In Phase 3, striping work begins. Details are provided in Appendix D and will include all ADA stalls as well as van accessible stalls. Both new vegetated areas and new planters require landscaping. Details for the planter layers are shown in Appendix D. Students suggest an additional bike rack be installed in the existing area for bikes. Light installation is scheduled for this phase. The foundation for the light poles is sufficient to sustain a maximum pole height of 30 feet.
- In Phase 4, the project will be finalized. Cleaning and inspection are included in the finalization process.

4.0 Regulatory Compliance and Permitting

This section describes the regulatory agencies considered for the stormwater improvement project.

4.1 CITY OF SILVERTON (CITY ENGINEERING DESIGN STANDARDS)

The City of Silverton has municipal standards and requirements for construction and design. Design standards include parking layout, disabled stalls, bike corrals, and the required amount of parking spaces for a recreational building.

4.2 OREGON TRANSPORTATION COMMISSION (STANDARDS FOR ACCESSIBLE PARKING PLACES AUGUST 2018)

The Oregon Transportation Commission (OTC), in accordance with the Oregon Revised Statute (ORS) 447.233, adopted standards for accessible parking spaces on January 22, 1992. ORS 447.223 states that all new construction and

re-striping of accessible parking spaces must comply with state requirements. Students reviewed and incorporated these regulations, which included stripe thickness, stripe locations, height for disabled stall signs, and signage types, among others.

4.3 DEPARTMENT OF ENVIRONMENTAL QUALITY

The Oregon Department of Environmental Quality (DEQ) is an environmental regulatory agency. It provides National Pollution Discharge Systems (NPDES) permits for Section 401 Water Quality Certification for Post-Construction Stormwater Management. Any design proposed in this project will create minimal runoff into Silver Creek, in compliance with DEQ requirements.

5.0 Conclusion

The proposed design focuses on expanding the existing YMCA pool parking lot while using the design as an opportunity to incorporate green infrastructure that mitigates and treats stormwater runoff.

The expansion will increase the total number of parking spaces from 44 to 56 while maintaining an efficient and safe layout for both passenger and emergency vehicles to navigate through the lot. The main benefit of this design is the addition of green infrastructure. By removing the oil separator from the existing lot and incorporating infiltration planters, runoff can be treated for any contaminants it is carrying. Furthermore, the porous pavement serves the same treatment purpose for runoff while removing any ponding that may occur from traditional pavement. The project's major limitation was not being able to incorporate more parking spaces due to the green space surrounding the existing lot. Students

avoided the removal of large trees and felt that protecting the current trees outweighed additional parking spaces.

As the city of Silverton and Keller Associates move forward on the project, students would like to highlight some next steps to complete the design. There are several important factors that still need to be considered and/or designed. First, the grading of asphalt in the area highlighted on sheet 4 of the plan set needs to be measured. Second, the routing of the planters' outflow pipes to the existing pipes of the removed oil separator need to be designed to account for stormwater during large events. Lastly, the right-of-way boundaries are assumed and will need to be verified before construction.

References

References pertaining to project research used for the project report are listed below. These references contain web links where the information can be retrieved and accessed for any further clarification.

Leger, R. J. (2015, May 27). Slopes V Innovative Ways to Show Storm Water Quality Compliance. Retrieved February 25, 2020, from <http://oregonewrg.org/wp-content/uploads/2015/05/SLOPES-V-Innovative-Ways-to-Show-Storm-Water-Quality-Compliance-FULL....pdf>

Oregon Transportation Commission Standards for Accessible Parking Places August 2018. (2018, August). Retrieved February 25, 2020, from https://www.oregon.gov/odot/Engineering/DOCS_ADA/ADA_Standards-Accessible-Parking.pdf

Section 401 Water Quality Certification. (2018, March). Retrieved February 25, 2020, from <https://www.oregon.gov/deq/FilterDocs/401wqcertPostCon.pdf>

Slopes V Stormwater Requirements Summary. (2017, February). Retrieved February 2020, from <http://trwc.org/wp-content/uploads/2017/02/SLOPES-V-Stormwater-Requirements2.pdf>

PRK-2.04-Replanting Requirements for Tree Removal on Private Property, City-Owned and Managed Sites and public rights-of-Way. (2015, January). Retrieved May 2020, from <https://www.portlandoregon.gov/citycode/article/526733>

Appendices

The following appendices are attached.

A. CONSTRUCTION COST ESTIMATE

This section presents the list of materials and construction activities with estimated costs.

B. CONSTRUCTION SCHEDULE

This section presents a list of tasks, subtasks in a Gantt chart for the estimated time for preconstruction and construction.

C. DEMOLITION PLAN

This section provides details on the steps/precautions needed before construction begins.

D. DRAWINGS

Preliminary design sheets for proposed design.

E. CALCULATIONS

This section includes supporting calculations done for the light pole foundation bearing capacity, infiltration planter runoff capacity and planter bearing capacity of the walls and HydroCAD runoff analysis for the porous pavement.

F. QC CHECKLIST

This section presents a quality control checklist to ensure the rubric and group requirements are met.

Appendix A

Construction Cost Estimate

Cost Estimate Report

Date: 05/31/2020

Stormwater Improvement Project

Year 2020 Quarter 2

Unit Detail Report

Prepared By: Melissa Boell

Portland State University

| LineNumber | Description | Quantity | Unit | Total Incl. O&P | Ext. Total Incl. O&P |
|--|---|----------|-------|-------------------|----------------------|
| Division 01 General Requirements | | | | | |
| 015433200100 | Rent excavator diesel hydraulic crawler mounted 1/2 CY capacity, Incl. Hourly Oper. Cost. | 4.00 | Day | \$702.11 | \$2,808.43 |
| 015433200482 | Rent backhoe-loader attachment, compactor, 20,000 lb., Incl. Hourly Oper. Cost. | 3.00 | Day | \$227.00 | \$680.99 |
| 015433201910 | Rent grader, self-propelled, 30,000 lb, Incl. Hourly Oper. Cost. | 2.00 | Day | \$1,745.79 | \$3,491.58 |
| 015433203000 | Rent roller, vibratory, tandem, smooth drum, 20 H.P., Incl. Hourly Oper. Cost. | 2.00 | Day | \$420.46 | \$840.93 |
| 015433204880 | Rent loader, skid steer, wheeled, 10 CF, 30 HP, Incl. Hourly Oper. Cost. | 2.00 | Day | \$269.85 | \$539.70 |
| 015433401680 | Rent barricade, portable with flasher 25 to 50 units, Incl. Hourly Oper. Cost. | 3.00 | Month | \$64.13 | \$192.39 |
| 015433404020 | Rent paver bituminous, rubber tires 8'wide 50 HP, diesel, Incl. Hourly Oper. Cost. | 1.00 | Day | \$907.98 | \$907.98 |
| Division 01 General Requirements Subtotal | | | | \$9,462.00 | |
| Division 02 Existing Conditions | | | | | |
| 022113090020 | Topographical survey, conventional, minimum | 2.00 | Acre | \$660.75 | \$1,321.50 |
| 023213100020 | Subsurface investigation, boring and exploratory drilling, initial field stake out & determination of elevations, for borings | 1.00 | Day | \$1,309.00 | \$1,309.00 |
| 024113176000 | Demolish, remove pavement & curb, remove concrete curbs, plain, excludes hauling and disposal fees | 130.00 | L.F. | \$5.22 | \$678.60 |
| 024119250020 | Selective demolition, saw cutting, each additional inch of depth over 3" | 40.00 | L.F. | \$1.37 | \$54.80 |
| 024210202500 | Deconstruction of wood components, posts, up to 2 stories, excludes handling, packaging or disposal costs | 40.00 | L.F. | \$1.27 | \$50.80 |
| Division 02 Existing Conditions Subtotal | | | | \$3,414.70 | |

| LineNumber | Description | Quantity | Unit | Total Incl. O&P | Ext. Total Incl. O&P |
|--------------------|---|----------|------|-----------------|----------------------|
| Division 03 | Concrete | | | | |
| 033053401020 | Structural concrete, in place, column (4000 psi), square, up to 2% reinforcing by area, 36" x 36", includes forms(4 uses), Grade 60 rebar, concrete (Portland cement Type 1), placing and finishing | 12.00 | C.Y. | \$1,175.50 | \$14,106.00 |
| Division 03 | Concrete Subtotal | | | | \$14,106.00 |
| Division 07 | Thermal and Moisture Protection | | | | |
| 071213100100 | Bentolite, rolls, with geotextile fabric both sides, 3/8" thick | 4,530.00 | S.F. | \$3.07 | \$13,907.10 |
| Division 07 | Thermal and Moisture Protection Subtotal | | | | \$13,907.10 |
| Division 10 | Specialties | | | | |
| 101453200100 | Signs, stock, aluminum, reflectorized, high intensity, .080" aluminum, 24" x 24", excludes posts | 3.00 | Ea. | \$151.05 | \$453.15 |
| Division 10 | Specialties Subtotal | | | | \$453.15 |
| Division 26 | Electrical | | | | |
| 260505100100 | Conduit, rigid galvanized steel, 1/2" to 1" diameter, electrical demolition, remove conduit to 10' high, including fittings & hangers | 40.00 | L.F. | \$3.02 | \$120.80 |
| 265613103000 | Light poles, anchor base, aluminum, 20' high, excl concrete bases | 6.00 | Ea. | \$1,901.50 | \$11,409.00 |
| Division 26 | Electrical Subtotal | | | | \$11,529.80 |
| Division 31 | Earthwork | | | | |
| 311313203100 | Selective clearing and grubbing, 8" to 12" diameter, remove selective trees, on site using chain saws and chipper, excludes stumps | 3.00 | Ea. | \$420.00 | \$1,260.00 |
| Division 31 | Earthwork Subtotal | | | | \$1,260.00 |
| Division 32 | Exterior Improvements | | | | |
| 321216140020 | Asphaltic concrete paving, parking lots & driveways, 6" stone base, 2" binder course, 1" topping, no asphalt hauling included | 4,530.00 | S.F. | \$2.78 | \$12,593.40 |
| 321613130300 | Cast-in place concrete curbs & gutters, concrete, wood forms, straight, 6" x 18", excludes concrete | 560.00 | L.F. | \$10.92 | \$6,115.20 |
| 321223130600 | Painted pavement markings, acrylic waterborne, white or yellow, 8" wide, less than 3,000 LF | 400.00 | L.F. | \$0.67 | \$268.00 |
| 323333100012 | Planters, precast concrete, sandblasted, 48" diameter, 24" high | 5.00 | Ea. | \$772.50 | \$3,862.50 |
| 329313100012 | Ground cover, plants, patchy/sandra, excludes preparation of beds | 5.00 | C | \$200.00 | \$1,000.00 |
| Division 32 | Exterior Improvements Subtotal | | | | \$23,839.10 |
| Division 33 | Utilities | | | | |

| LineNumber | Description | Quantity | Unit | Total Incl. O&P | Ext. Total Incl. O&P |
|--------------------|---|----------|------|-----------------|----------------------|
| 334211402040 | Public storm utility drainage piping, corrugated metal pipe, galvanized and bituminous coated with paved invert, 20' lengths, 16 ga., 8" diameter, excludes excavation and backfill | 15.00 | L.F. | \$19.51 | \$292.65 |
| Division 33 | Utilities Subtotal | | | | \$292.65 |
| Subtotal | | | | | \$78,264.50 |
| | General Contractor's Markup on Subs | | | 0.00% | \$0.00 |
| Subtotal | | | | | \$78,264.50 |
| | General Conditions | | | 0.00% | \$0.00 |
| Subtotal | | | | | \$78,264.50 |
| | General Contractor's Overhead and Profit | | | 0.00% | \$0.00 |
| Grand Total | | | | | \$78,264.50 |


Appendix B

Construction Schedule

Design Report (Draft III)
Appendix B

Figure B.1 Construction Schedule.

| 1000 | Phase 0 Preconstruction (c06/01/20 to 06/16/20, Duration 12 days) | | | |
|-------------|--|------------------|--------------------|-----------------|
| Task | Title | StartDate | Finish Date | Duration |
| 1010 | Design and planning | 06/01/20 | 06/12/20 | 10 days |
| 1020 | Design approval | 06/15/20 | 06/15/20 | 1 day |
| 1030 | Contract execution | 06/16/20 | 06/16/20 | 1 day |
| 1040 | Phase exit review | | | |
| 2000 | Construction (06/17/20 to 07/15/20, Duration 21 days) | | | |
| Task | Phase 1 (8 days) | StartDate | Finish Date | Time |
| 2010 | Equipment mobilization | 06/17/20 | 06/17/20 | 1 day |
| 2020 | Erosion control | 06/18/20 | 06/18/20 | 1 day |
| 2030 | Demolition & Removal | 06/19/20 | 06/19/20 | 1 day |
| 2040 | Grading | 06/22/20 | 06/23/20 | 2 days |
| 2050 | Underground piping (Stormwater) | 06/24/20 | 06/24/20 | 1 day |
| 2060 | Utilities (light poles) | 06/25/20 | 06/26/20 | 2 day |
| 2070 | Phase exit review | | | |
| Task | Phase 2 (9 days) | StartDate | Finish Date | Time |
| 3010 | Concrete work (Curbs) | 06/29/20 | 06/30/20 | 2 days |
| 3020 | Concrete work (Planter walls) | 07/01/20 | 07/02/20 | 2 days |
| 3030 | Concrete work (Light pole foundation) | 07/03/20 | 07/06/20 | 2 days |
| 3040 | Ground preparation | 07/07/20 | 07/07/20 | 1 day |
| 3050 | Geosynthetic mesh | 07/08/20 | 07/08/20 | 1 day |
| 3060 | Asphalt installation | 07/09/20 | 07/09/20 | 1 day |
| 3070 | Phase exit review | | | |
| Task | Phase 3 (3 days) | StartDate | Finish Date | Time |
| 4010 | Stripping work | 07/10/20 | 07/10/20 | 1 day |
| 4020 | Landscape planter and green areas | 07/13/20 | 07/13/20 | 1 day |
| 4030 | Bike rack installation | 07/14/20 | 07/14/20 | 1 day |
| 4040 | Light installation | 07/14/20 | 07/15/20 | 1 day |
| 4050 | Phase exit review | | | |
| Task | Phase 4 (2 days) | StartDate | Finish Date | Time |
| 4040 | Project clean up | 07/15/20 | 07/15/20 | 1 day |
| 4050 | Project completion & inspection | 07/26/20 | 07/16/20 | 1 day |
| 4060 | Phase exit review | | | |




Appendix C

Drawings

CITY OF SILVERTON, OREGON STORMWATER IMPROVEMENTS

2020.SILV.01 PLANS FOR PROPOSED PROJECT
JUNE - 2020



VICINITY MAP
NO SCALE

| DATE | REVISION | BY |
|------|----------|----|
| | | |
| | | |
| | | |
| | | |

DO NOT SCALE THIS DRAWING
FOLLOW DIMENSIONS INDICATED
ON SCALES CORRECT ONLY FOR
FULL SIZE SHEET (22 X34)



ATTENTION:
Oregon Law Requires You To Follow Rules
Adopted By The Oregon Utility Notification Center.
Those Rules Are Set Forth In OAR 952-001-0010 Through
OAR 952-001-0090. You May Obtain Copies Of The Rules From The Center.




| SHEET NO. | DESCRIPTION |
|-----------|--|
| 1 | COVER PAGE |
| 2 | GENERAL NOTES |
| 3 | EXISTING PARKING LOT PLAN |
| 4 | DEMOLITION PLAN |
| 5 | PROPOSED PARKING LOT ADDITION |
| 6 | STRIPING PLAN |
| 7 | DETAILS SHEET 1 (RAIN GARDEN/LIGHTING) |
| 8 | DETAILS SHEET 2 (PARKING STALL/ROAD) |
| 9 | PASSENGER VEHICLE TEMPLATE |
| 10 | EMERGENCY VEHICLE TEMPLATE |

| | |
|---|--|
| <p>Maseeh College of Engineering and Computer Science PORTLAND STATE UNIVERSITY</p> | |
| DRAFTER: _____ DESIGNER: _____ GRR: _____ CHECKER: _____ REVIEWER: _____ | COVER PAGE STORMWATER IMPROVEMENTS 2020.SILV.01 INDEX OF SHEETS |
| SHEET NO. 1/10 | 1/10 |

GENERAL NOTES

1. All Construction, materials, and workmanship shall conform to the latest standards and practices of the City of Silverton, Oregon and the "Standard Specifications for Road and Municipal Construction."
 - 1) Unless otherwise approved by the Public Works Director, materials shall conform to the minimum requirements outlined herein and as shown on the Standard Details. This listing is not intended to be complete nor designed to replace the City's Public Works Construction Standards (PWCS).
 - 2) In the case of conflicts between the provisions of these design standards and the PWCS, the more stringent as determined by the Public Works Director shall apply. Acceptable materials shall be as outlined in these Design Standards.
 - 3) It is not intended that materials listed herein are to be considered acceptable for all applications. The design engineer shall determine the materials suitable for the project to the satisfaction of the Public Works Director.
2. Where existing services must be interrupted, the Contractor shall obtain approval from the construction manager's officer and notify all customers that are to be affected as to the date, time, and duration of the interruption. Notification must be done 24 hours in advance of the interruption. The Contractor shall schedule construction to provide minimum interruption of services as determined by the inspector. Under no circumstances will the Contractor schedule a water main shut down without the required 24 hour notice. The Contractor shall not operate the City of Silverton's water facilities without approval from the construction inspector.
3. All materials shall meet the applicable specifications in the City of Silverton standards. Before any native material is used, tests results shall be provided to the City Inspector indicating that the material meets the specifications. Backfill material shall be compacted to 95% of the maximum relative density.
4. The Contractor shall notify the City of Silverton's construction manager's office, County, ODOT and all utility companies a minimum of 48 hours prior to the start of construction. Inspections and approval of the construction will be by the City construction manager's officer. A satisfactory pressure and bacteriological test for any water construction is required for approval and comply with all other requirements of ORS 757.541 to 757.571.
5. The Contractor shall have all existing utilities properly located prior to commencing excavations. The Contractor shall, at a minimum, call 48 hours before beginning excavations.
6. The existing underground utilities shown on these plans were all that had been constructed at the time these plans were completed. Additional underground construction may have occurred before construction of this project was started. Notice shall be given to the owners of the facilities not less than two business days or more than 10 business days before excavation.
7. All construction within existing City of Silverton right-of-way shall have an approved traffic control plan prior to any on-site construction activity.
8. Pre-paving as-builts shall be submitted to the City of Silverton Development Review Services Department and City Inspector for sanitary sewer, storm sewer, and storm facilities prior to paving.
9. Any significant deviations from the plans will require a request from the applicant's engineer and approval from the City's Transportation Division engineer(s) and City Inspector.
10. Should any item of archeological interest be found during development, you are required to stop work and notify the planning case manager immediately. Failure to do so could result in a felony conviction.
11. Soil and subgrade construction requires inspector approve proof roll and/or testing prior to rocking and prior to paving.
12. All traffic control plans & measures shall be approved by the agency with jurisdiction and in place prior to any construction activity. Contractor shall erect and maintain barriers, warning signs, traffic cones (and all other traffic control devices required) per City, County and ODOT requirements in accordance with the current MUTCD (including Oregon amendments). Access to driveways and buildings shall be maintained at all times for residential, fire and emergency vehicles.
13. Record Drawings: The Contractor shall maintain one complete set of approved drawings on the construction site at all times whereon he will record any approved deviations in construction from the approved drawings, as well as the station locations and depths of all existing utilities encountered (whether or not existing utilities are shown on the construction drawings). These field record drawings shall be kept up to date at all times and shall be available for inspection by the City upon request. Information on the field record drawings shall include reference measurements and materials type.



| |
|--|
|  Maseeh College of Engineering and Computer Science <small>PORTLAND STATE UNIVERSITY</small> |
| DRAWER: _____ CHECKER: _____ DESIGNER: _____ REVIEWER: _____ |
| STORMWATER IMPROVEMENTS 2020.SILV.01 |
| GENERAL NOTES SHEET 2/10 |



DO NOT SCALE THIS DRAWING
 SOLID DIMENSIONS UNLESS NOTED
 FULL SIZE SHEET (22" X 34")



| NO. | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

| DATE | REVISION | BY |
|------|----------|----|
| | | |
| | | |
| | | |
| | | |
| | | |

EXTG. YMCA PARKING LOT PLAN
SCALE: 1" = 20' 0"

DO NOT SCALE THIS DRAWING
FOLLOW DIMENSIONS, INDICATED
SCALES CORRECT ONLY FOR
FULL SIZE SHEET (22 X34")

PLOT DATE: 5/23/2020 PLOT TIME: 8:11 PM USER: GREGES



NOTE:
EXTG. PARKING STALL
CONDITIONS @ 4.90°
VARY IN LENGTHS.
R/W IS ASSUMED.
VERIFY FOR ACTUAL
LOCATION.

LEGEND

- EXTG. CURB
- - - ASSUMED R/W LINE
- — — EXTG. CONCRETE PATH
- — — EXTG. PARKING STRIPING

**Maseeh College of Engineering
and Computer Science**
PORTLAND STATE UNIVERSITY

| | |
|-----------------|-------------------|
| DRAWN BY: _____ | CHECKED BY: _____ |
| DESIGNER: _____ | REVIEWER: _____ |

STORMWATER IMPROVEMENTS
2020.SILV.01


| | |
|-----------------------------------|-----------------------------|
| EXISTING PARKING LOT PLAN VIEW | SHEET NO. 3/10 |
|-----------------------------------|-----------------------------|

PLOT DATE: 9/23/2020 PLOT TIME: 9:20 PM USER: GRETES

| NO. | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

PROP. PARKING LOT PLAN
SCALE: 1" = 20'

DO NOT SCALE THIS DRAWING
FOLLOW DIMENSIONS. INDICATED
SCALES CORRECT ONLY FOR
FULL SIZE SHEET (22 X34")



Maseeh College of Engineering and Computer Science
FORT LANE STATE UNIVERSITY

PROJECT: STORMWATER IMPROVEMENTS
2020.SILV.01

PROPOSED PARKING LOT EXPANSION

SHEET NO. 5/10


LEGEND

| DETAIL CALLOUT | DESCRIPTION |
|----------------|---------------------------------|
| (1) | LIGHT POLE FOUNDATION |
| (2) | DETAIL PG. 5, RAIN GARDEN |
| (3) | INSTALL 6'X25' RAIN GARDEN |
| (4) | INSTALL 6'X45' RAIN GARDEN |
| (5) | PER DETAIL PG. 9 |
| (6) | EXISTING BIKE RACK |
| (7) | PROPOSED BIKE RACK |
| (8) | PROPOSED CURB |
| (9) | PROPOSED PARKING SPACE STRIPING |
| (10) | EXTG. CURB |
| (11) | ASSUMED R/W LINE |
| (12) | ASPHALT CROWN |

PARKING

- 57 PARKING SPACES OVERALL
- 45 EXISTING PARKING SPACES
- 12 PROPOSED PARKING SPACES

(SEE DETAIL SHEET 9 FOR PROP. PARKING SPACE DIMENSIONS).




| NO. | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

STRIPING PLAN
SCALE: 1" = 20'0"

DO NOT SCALE THIS DRAWING
FOLLOW DIMENSIONS INDICATED
SCALES CORRECT ONLY FOR
PLOT SIZE SHEET (22 X34")

DATE: 9/23/2020
PLOT TIME: 2:25 PM
USER: GREYES



PARKING

57 PARKING SPACES OVERALL
45 EXISTING PARKING SPACES
12 PROPOSED PARKING SPACES

(SEE DETAIL SHEET 9 FOR PROP. PARKING SPACE DIMENSIONS).

| DETAIL CALLOUT | DESCRIPTION |
|----------------|---|
| (E7) | EXTG. PARKING SPACE STRIPES 90° ANGLE |
| (P1) | PROPOSED PARKING SPACE STRIPES 45° DIAGONAL |
| (P2) | PROPOSED PARKING SPACE STRIPES 90° ANGLE |
| (A1) | PROPOSED PARKING TRAFFIC DIRECTION |
| (A2) | ADA PROP. PARKING SPACE |
| (A3) | PROPOSED CURB |
| (A4) | PROPOSED PARKING SPACE STRIPING |
| (A5) | EXTG. CURB |
| (A6) | ASSUMED R/W LINE |



Maseeh College of Engineering and Computer Science
PORTLAND STATE UNIVERSITY

DESIGNER: _____ CHECKER: _____
REVISOR: _____

STORMWATER IMPROVEMENTS
2020.SILV.01


PROPOSED PARKING LOT STRIPING PLAN

SHEET NO. 6/10

| NO. | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

DO NOT SCALE THIS DRAWING
 DIMENSIONS AND
 SCALES CORRECT ONLY FOR
 FULL SIZE SHEET (22"X34")

- LEGEND**
- EXISTING CURB
 - ASSUMED R/W
 - PROP. TURNING TRACECTORY
 - PROP. CURB
 - PROP. PARKING STALLS



 Maseeh College of Engineering
 and Computer Science
 PORTLAND STATE UNIVERSITY


DRAWN BY: _____ CHECKED BY: _____
 DESIGNED BY: _____ REVISIONS: _____

STORMWATER IMPROVEMENTS
 2020.SILV.01
PASSENGER VEHICLE
TURNING DIAGRAM

SHEET
 NO. 9/10

| NO. | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

DO NOT SCALE THIS DRAWING
FOLLOW DIMENSIONS, INDICATED
SCALES CORRECT ONLY FOR
FULL SIZE SHEET (22 X 34")



LEGEND

- EXISTING CURB
- ASSUMED R/W
- PROP. TURNING TRAJECTORY
- PROP. CURB
- PROP. PARKING STALLS



Maseeh College of Engineering
and Computer Science
PORTLAND STATE UNIVERSITY

DEPARTMENT: GRS OFFICE: _____
DESIGNER: _____ REVIEWER: _____

STORMWATER IMPROVEMENTS
2020.SILV.01

EMERGENCY VEHICLE
TURNING DIAGRAM

SHEET NO.
10/10

Appendix D

Calculations


D. Calculation

D.1 Light Pole Foundation Calculations

D.2 Infiltration Planter Analysis

D.3 Planter Wall Bearing Capacity Calculations.

POLE FOUNDATION ANALYSIS
 For free-Top (unconstrained) Rigid Round Piers Using IBC Code Method
 Subjected to Vertical Load, Horizontal Load, and/or Moment.



Nomenclature

Table A1. IBC 2012 - Presumptive Load Bearing Values

| Class of Materials | Vertical Foundation Pressure | Lateral Bearing Pressure (below natural grade) |
|---|------------------------------|--|
| | (ksf) | (ksf/ft.) |
| 1. Crystalline bedrock | 12.000 | 1.200 |
| 2. Sedimentary and foliated rock | 4.000 | 0.400 |
| 3. Sandy gravel and/or gravel | 3.000 | 0.200 |
| 4. Sand, silty sand, clayey sand, silty gravel and clayey gravel | 2.000 | 0.150 |
| 5. Clay, sandy clay, silty clay, clayey silt, silt and sandy silt | 1.500 | 0.100 |

Table A.2 PBOT Standard Street Light Pole Footing (Standard Drawing P-660) - Presumptive Values

| Description | Value |
|--------------------------|---------|
| 1. Friction Angle f | 26° |
| 2. Effective Unit Weight | 110 pcf |

Table A.3 (AASHTO 2001) Wind Pressure

$$P_z = 0.00256(1.3V_{fm})^2 C_d C_h$$

Description

| | | |
|-------------------------------------|----------------|---------|
| Fastest-mile wind speed | V_{fm} | 120mph |
| Drag coefficient | C_d | 1 |
| Coefficient for height above ground | C_h | 0.5 |
| Design wind Pressure | P_z or P_h | 608 psf |

Input Data:
Pier Data:

Pier Foundation Diameter, $D = 2.000$ ft.
 Pier Height Above Soil, $h_1 = 2.000$ ft.

Soil Data:

Unit Weight of Soil, $g = 0.120$ kcf
 Angle of Internal Friction, $f = 26.00$ deg.
 Depth to Resisting Surface, $h_2 = 0.000$ ft.
 Allow. Vert. Bearing Pressure, $P_a = 3.000$ ksf

Pier Loadings:

Axial Load, $P_v = 2.200$ kips
 Horizontal Load, $P_h = 0.610$ kips
 Distance from P_h to Top/Pier, $H = 10.000$ ft.
 Externally Applied Moment, $M = 0.000$ ft-kips

Results:

Pier Embedment and Total Length:

| | | | |
|-------|-------|-----|---|
| Pe = | 0.610 | kip | Pe = Ph+(M/(H+h1+h2)) ("equivalent total" horizontal load) |
| Pba = | 0.200 | ksf | Pba = allowable lateral bearing pressure/ft. below grade (Table 1806.2) |
| S1 = | 0.392 | ksf | S1 = Pba*L/3 (allowable lateral soil pressure at 1/3 embedment depth) |
| A = | 1.822 | | A = 2.34*Pe/(S1*D) |
| L = | 5.88 | ft. | L = 0.5*A*(1+SQRT(1+(4.36*(H+h1+h2)/A))) (IBC 2012 Eqn. 18.1) |
| Lt = | 7.88 | ft. | Lt = h1+h2+L (total length) |

Pier End Bearing Pressure:

| | | | |
|----------|-------|-------|-----------------------------------|
| Af = | 3.14 | ft.^2 | Af = p*D^2/4 (pier base area) |
| Wf = | 3.71 | kip | Wf = (Af*Lt)*0.150 (pier weight) |
| SPv = | 5.91 | kip | SPv = Pv+Wf (total vertical load) |
| P(bot) = | 1.882 | ksf | P(bot) = SPv/Af |

Pa>=P(bot), O.K.

Reference: 2012 International Building Code (IBC), Section 1807.3.2.1, pages 403-404

**Infiltration Planter Analysis for size and infiltration capacity for a 2, 10- and 15-year storm event.
 Presumptive Approach Calculator (PAC) Data Sheets.**

Designer's Statement

The Silverton Stormwater improvement infiltration Planter Analysis was prepared by Abraham Salazar, meeting City of Silverton minimum Standards and normal Engineering standards.

Project Name: 2020.SILV.01
 Project Address: 421 S Water St Silverton, OR 97381
 Designer: Abraham Salazar
 Last Modified: 5/20/20 1:27 PM
 Company: Portland State University
 Report Generated: 5/20/20 1:27 PM
 Catchment ID: Infiltration Planter


PAC

Facility Details

Facility Type: Planter (Flat)




Facility Configuration: C: Infl. with RS and underdrain (Ud)



Catchment ID: 1
 Catchment Name: Infiltration Planter
 Catchment Impervious Area: 14,000 sq ft
 Hierarchy Category: 3
 Hierarchy Description: Off-site flow to drainageway, river, or storm-only pipe system

Facility Shape



Results

| <p>Pollution Reduction</p> <p style="font-size: 2em; color: green; font-weight: bold;">PASS</p> | <p>Overflow Volume</p> <p>Surface Capacity Used 10%</p> <p>Rock Capacity Used 0%</p> | | | | | | | | | | | | | | | | | | | | |
|--|--|--------|-----------------------------------|--------|---------------------------------|--------|-------|---|-------|--------|-------|---|-------|---------|------|---|-------|---------|-------|---|-------|
| <p>Flow Control</p> <p style="font-size: 2em; color: green; font-weight: bold;">PASS</p> | <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center; border: 1px solid black;">POST-DEVELOPMENT OUTFLOW (CFS)</th> <th style="text-align: center;">≤ ½ of</th> <th style="text-align: center; border: 1px solid black;">PRE-DEVELOPMENT INFLOW (CFS)</th> </tr> </thead> <tbody> <tr> <td style="text-align: left;">2 year</td> <td style="text-align: center; border: 1px solid black;">0.077</td> <td style="text-align: center;">≤</td> <td style="text-align: center; border: 1px solid black;">0.198</td> </tr> <tr> <td style="text-align: left;">5 year</td> <td style="text-align: center; border: 1px solid black;">0.216</td> <td style="text-align: center;">≤</td> <td style="text-align: center; border: 1px solid black;">0.241</td> </tr> <tr> <td style="text-align: left;">10 year</td> <td style="text-align: center; border: 1px solid black;">0.26</td> <td style="text-align: center;">≤</td> <td style="text-align: center; border: 1px solid black;">0.285</td> </tr> <tr> <td style="text-align: left;">25 year</td> <td style="text-align: center; border: 1px solid black;">0.303</td> <td style="text-align: center;">≤</td> <td style="text-align: center; border: 1px solid black;">0.328</td> </tr> </tbody> </table> | | POST-DEVELOPMENT OUTFLOW (CFS) | ≤ ½ of | PRE-DEVELOPMENT INFLOW (CFS) | 2 year | 0.077 | ≤ | 0.198 | 5 year | 0.216 | ≤ | 0.241 | 10 year | 0.26 | ≤ | 0.285 | 25 year | 0.303 | ≤ | 0.328 |
| | POST-DEVELOPMENT OUTFLOW (CFS) | ≤ ½ of | PRE-DEVELOPMENT INFLOW (CFS) | | | | | | | | | | | | | | | | | | |
| 2 year | 0.077 | ≤ | 0.198 | | | | | | | | | | | | | | | | | | |
| 5 year | 0.216 | ≤ | 0.241 | | | | | | | | | | | | | | | | | | |
| 10 year | 0.26 | ≤ | 0.285 | | | | | | | | | | | | | | | | | | |
| 25 year | 0.303 | ≤ | 0.328 | | | | | | | | | | | | | | | | | | |

Project Summary

Infiltration garden for YMCA storm water improvements

| Catchment Name | Impervious Area (sq ft) | Native Soil Design Infiltration Rate | Hierarchy Category | Facility Type | Facility Config | Facility Size (sq ft) | Facility Sizing Ratio | PR Results | Flow Control Results |
|----------------------|-------------------------|--------------------------------------|--------------------|----------------|-----------------|-----------------------|-----------------------|------------|----------------------|
| Infiltration Planter | 14000 | 5.00 | 3 | Planter (Flat) | C | 543 | 3.9% | Pass | Pass |


Catchment Infiltration Planter

| Site Soils & Infiltration Testing Data | Infiltration Testing Procedure | Open Pit Falling Head |
|--|--|---|
| | Native Soil Infiltration Rate (I_{test}) | 5.00 |
| Correction Factor | CF_{test} | 2 |
| Design Infiltration Rates | Native Soil (I_{dsgn}) | 2.50 in/hr |
| | Imported Growing Medium | 2.00 in/hr |
| Catchment Information | Hierarchy Category | 3 |
| | Disposal Point | B |
| | Hierarchy Description | Off-site flow to drainageway, river, or storm-only pipe system |
| | Pollution Reduction Requirement | Pass |
| | 10-year Storm Requirement | N/A |

Design Report (Draft III)
Appendix D

| | |
|---|---|
| Flow Control Requirement | If discharging to an overland drainage system or to a storm sewer that discharges to an overland drainage system, including streams, drainageways, and ditches, the 2-year post-development peak flow must be equal or less than half of the 2-year pre-development rate and the 5, 10, and 25-year post-development peak rate must be equal or less than the pre-development rates for the corresponding design storms. |
| Impervious Area | 14000 sq ft 0.321 acre |
| Time of Concentration (Tc) | 5 |
| Pre-Development Curve Number (CN _{pre}) | 98 |
| Post-Development Curve Number (CN _{post}) | 98 |

SBUH Results



| | Pre-Development Rate and Volume | | Post-Development Rate and Volume | |
|--------------|---------------------------------|-------------|----------------------------------|-------------|
| | Peak Rate (cfs) | Volume (cf) | Peak Rate (cfs) | Volume (cf) |
| PR | 0.058 | 731.539 | 0.058 | 731.539 |
| 2 yr | 0.198 | 2533.242 | 0.198 | 2533.242 |
| 5 yr | 0.241 | 3113.481 | 0.241 | 3113.481 |
| 10 yr | 0.285 | 3694.589 | 0.285 | 3694.589 |
| 25 yr | 0.328 | 4276.244 | 0.328 | 4276.244 |


Facility Infiltration Planter

| Facility Details | Facility Type | Planter (Flat) |
|---------------------------------|--|---|
| | Facility Configuration | C: Infl. with RS and underdrain (Ud) |
| | Facility Shape | Planter |
| Above Grade Storage Data | | |
| | Bottom Area | 543 sq ft |
| | Bottom Width | 6.00 ft |
| | Storage Depth 1 | 10.0 in |
| | Growing Medium Depth | 18 in |
| | Surface Capacity at Depth 1 | 452.5 cu ft |
| | Design Infiltration Rate for Native Soil | 0.031 in/hr |
| | Infiltration Capacity | 0.025 cfs |
| Below Grade Storage Data | | |
| | Rock Storage Depth | 18 in |
| | Rock Porosity | 0.38 in |
| | Storage Depth 3 | 15.0 in |

| | | |
|------------------------------------|---|---------------------|
| Facility Facts | Total Facility Area Including Freeboard | 543.00 sq ft |
| | Sizing Ratio | 3.9% |
| Pollution Reduction Results | Pollution Reduction Score | Pass |
| | Overflow Volume | 0.000 cf |
| | Surface Capacity Used | 10% |
| | Rock Capacity Used | 0% |
| Flow Control Results | Flow Control Score | Pass |
| | Overflow Volume | 1219.882 cf |
| | Surface Capacity Used | 100% |
| | Rock Capacity Used | 0% |


| | Post-development outflow (cfs) | | Pre-development inflow (cfs) | |
|--------------------|-----------------------------------|--------|---------------------------------|-------------|
| 2 year | 0.077 | ≤ ½ of | 0.198 | Pass |
| 5 year | 0.216 | ≤ | 0.241 | Pass |
| 10 year | 0.26 | ≤ | 0.285 | Pass |

Pollution Reduction Event Surface Facility Modeling



- Inflow from rain
- Total flow to below grade storage
- Percent surface capacity
- Infiltration capacity
- Flow bypassing growing medium

Pollution Reduction Event Below Grade Modeling



- Inflow to rock storage
- Overflow to approved discharge
- Infiltration capacity
- Percent rock capacity

25
year


0.303

≤

0.328


Pass

2 Year Event Surface Facility Modeling




- Inflow from rain
- Total flow to below grade storage
- Percent surface capacity
- Infiltration capacity
- Flow bypassing growing medium

2 Year Event Below Grade Modeling



- Inflow to rock storage
- Overflow to approved discharge
- Infiltration capacity
- Percent rock capacity



Analysis for Infiltration Planter Wall Design

Minimum footing width (B) was found and checked to satisfy requirements for design using Rankine's Theory for earth pressure coefficients.




Figure D.1 Planter wall

Design Report (Draft III)
Appendix D

| | Trial 1 | Trial 2 | Trial 3 |
|-----------------------------------|---------|---------|---------|
| Assumed B (in) = | 4 | 6 | 8 |
| Assumed B (m) = | 0.1016 | 0.1524 | 0.2032 |
| L (in) = | 0 | 1 | 2 |
| L (m) = | 0 | 0.0254 | 0.0508 |
| Wall height, h (ft) = | 3.5 | 3.5 | 3.5 |
| Wall height, h (m) = | 0.97 | 0.97 | 0.97 |
| γ_f (kN/m ³) = | 20.0 | 20.0 | 20.0 |
| ϕ'_f (deg)= | 36 | 36 | 36 |
| γ_c (kN/m ³) = | 24 | 24 | 24 |
| H (ft) = | 4.5 | 4.5 | 4.5 |
| H (m) = | 1.37 | 1.37 | 1.37 |

Rankine active coefficient (Ka) = $\tan^2(45-\phi'/2)$

| | | | |
|---|------|--------|--------|
| Ka = | 0.26 | 0.26 | 0.26 |
| Surcharge q (kPa) = | 0 | 0 | 0 |
| Pa1 (kN) =q*Ka*H = | 0.0 | 0.0 | 0.0 |
| Arm of Pa1 to Point A (m) = | 0.0 | 0.0 | 0.0 |
| Pa2 (kN) = (1/2)*Ka* γ_f *H ² = | 4.9 | 4.9 | 4.9 |
| Arm of Pa2 to Point A (m) = | 0.46 | 0.46 | 0.46 |
| | | | |
| V1 (kN) = | 0.0 | 0.5 | 1.0 |
| Arm of V1 to Point A (m) = | 2.5 | 2.5127 | 2.5254 |
| V2 (kN) = | 0.0 | 0.0 | 0.0 |
| Arm of V2 to Point A (m) = | 2.5 | 2.5127 | 2.5254 |
| W1 (kN) = | 11.6 | 11.6 | 11.6 |
| Arm of W1 to Point A (m) = | 2.25 | 2.25 | 2.25 |
| W2 (kN) = | 30.0 | 30.3 | 30.6 |
| Arm of W2 to Point A (m) = | 1.25 | 1.2627 | 1.2754 |

Design Report (Draft III)
Appendix D

$$\Sigma F_{\text{horiz}} = 0 \rightarrow T = Pa1 + Pa2$$

| | | | |
|----------|-----|-----|-----|
| T (kN) = | 4.9 | 4.9 | 4.9 |
|----------|-----|-----|-----|

$$\Sigma F_{\text{vert}} = 0 \rightarrow N = V1 + V2 + W1 + W2$$

| | | | |
|----------|------|------|------|
| N (kN) = | 41.6 | 42.4 | 43.2 |
|----------|------|------|------|

$$\Sigma M_A = 0 \rightarrow x = (V1*arm + V2*arm + W1*arm + W2*arm - Pa1*arm - Pa2*arm)/N$$

| | | | |
|---------|------|------|------|
| x (m) = | 1.48 | 1.50 | 1.51 |
|---------|------|------|------|

(a) Check overturning

| | | | |
|------------------|-------|-------|-------|
| e (m) = B/2 - x | -1.43 | -1.42 | -1.41 |
| B/6 (m) = | 0.02 | 0.03 | 0.03 |
| e ≤ B/6 (Yes/No) | Yes | Yes | Yes |

(b) Check sliding

AASHTO Table 3.11.5.3-1 using mass concrete on coarse sand:

| | | | |
|--|------|------|------|
| δ (deg) = | 30 | 30 | 30 |
| Tult (kN) = N*tan(δ) = | 24.0 | 24.5 | 25.0 |
| FS _{sliding} = (Tult)/(Pa1+Pa2) = | 4.92 | 5.02 | 5.11 |
| FS _{sliding} ≥ 1.5 (Yes/No) | Yes | Yes | Yes |

(c) Check bearing

| | | | |
|--|-------|-------|-------|
| Known: q _{ult} (kPa) = | 650 | 650 | 650 |
| B' (m) = B - 2*e = | 2.95 | 2.99 | 3.03 |
| q _{avg} (kPa) = N/B' = | 14.1 | 14.2 | 14.3 |
| FS _{bearing} = q _{ult} /q _{avg} = | 46.08 | 45.81 | 45.54 |
| FS _{bearing} ≥ 3 (Yes/No) | Yes | Yes | Yes |

Therefore, the planter walls will be ok with thickness of: 4", 6" and 8". If 6" thick is used, more concrete can be saved.

Appendix E

QC Checklist

| Preparer | Checker | Checklist Item |
|----------|---------|--|
| X | X | 3.0 Facility Design |
| X | X | 3.1 Design Criteria |
| X | X | 3.2 Mitigation of Increased Runoff |
| X | X | 3.3 Mitigation of Current Runoff |
| X | X | 3.4 Additional Problems that Arose |
| X | X | 3.5 Construction Cost |
| X | X | 3.6 Construction Schedule |
| X | X | 4.0 Regulatory Compliance and Permitting |
| X | X | 4.1 City of Silverton (City Design Standards) |
| X | X | 4.2 Oregon Transportation Commission (Standards for Accessible Parking Places August 2018) |
| X | X | 4.3 Department of Environmental Quality (DEQ) |
| X | X | 5.0 Conclusion |
| X | X | References |
| X | X | APPENDICES |
| X | X | A: Construction Cost Estimate |
| X | X | B: Construction Schedule |
| X | X | C: Drawings |
| X | X | D: Calculations |
| X | X | E: QC Check list |

| | | | |
|-----------------|-----------------|----------------|-----------------|
| Preparer | Name: Abraham S | Signature: ASR | Date: 5/30/2020 |
|-----------------|-----------------|----------------|-----------------|

| | | | |
|----------------|---------------|----------------|-----------------|
| Checker | Name: Jacob E | Signature: J E | Date: 5/30/2020 |
|----------------|---------------|----------------|-----------------|

Design Report (Draft III)

| | |
|----------------------|---------------------------------|
| Group Project | Capstone Team (2020.SILV.01) |
|----------------------|---------------------------------|

| Preparer | Checker | Checklist Item |
|----------|---------|---|
| x | x | GENERAL |
| x | x | Grammar and Spelling |
| x | x | Single, combined PDF |
| x | x | Descriptive file name |
| x | x | Consistent formatting |
| x | x | Cover Page |
| x | x | Project Title and ID |
| x | x | Team # and Name |
| x | x | Team Members and Names |
| x | x | Client Name |
| x | x | Relevant Figure and Description |
| x | x | Table of Content |
| x | x | All sections, subsections listed with page numbers |
| x | x | Appendices listed with numbers |
| x | x | Executive Summary |
| x | x | 1.0 PROJECT UNDERSTANDING |
| x | x | 1.1 Existing Site Conditions |
| x | x | 1.2 Stake Holders |
| x | x | 2.0 Alternative Analysis |
| x | x | 2.1 Considered Alternatives |
| x | x | 2.1.1 Alternative 1: No build |
| x | x | 2.1.2 Alternative 2: Non-Permeable Asphalt |
| x | x | 2.1.3 Alternative 3: Permeable Asphalt for the expanded Area |
| x | x | 2.1.4 Alternative 4: Permeable Paver Stalls and Permeable Asphalt |
| x | x | 2.2 Selection Criteria |
| x | x | 2.2.1 Access |
| x | x | 2.2.2 Safety |
| x | x | 2.2.3 Environmental |
| x | x | 2.2.4 Aesthetics |
| x | x | 2.2.5 Maintenance |
| x | x | 2.2.6 Cost |

SILV.01_RUNOFF_ANALYSIS_2.0

Type IA 24-hr 10 - Yr Rainfall=3.83"

Prepared by HydroCAD SAMPLER 1-800-927-7246 www.hydrocad.net

Printed 5/31/2020

HydroCAD® 10.10-3a Sampler s/n S24281 © 2020 HydroCAD Software Solutions LLC

Page 7

This report was prepared with the free HydroCAD SAMPLER, which is licensed for evaluation and educational use ONLY. For actual design or modeling applications you MUST use a full version of HydroCAD which may be purchased at www.hydrocad.net. Full programs also include complete technical support, training materials, and additional features which are essential for actual design work.

Time span=0.00-30.00 hrs, dt=0.01 hrs, 3001 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind method - Pond routing by Stor-Ind method

Subcatchment 5S: PARKING LOT EAST Runoff Area=0.104 ac 100.00% Impervious Runoff Depth=3.60"
Tc=100.0 min CN=98 Runoff=0.05 cfs 0.031 af

Subcatchment 8S: Pre-Development Runoff Area=0.104 ac 0.00% Impervious Runoff Depth=1.34"
Tc=5.0 min CN=72 Runoff=0.03 cfs 0.012 af

Pond 4P: Pervious Pavement Peak Elev=-2.50' Storage=0.000 af Inflow=0.05 cfs 0.031 af
Outflow=0.05 cfs 0.031 af

Total Runoff Area = 0.208 ac Runoff Volume = 0.043 af Average Runoff Depth = 2.47"
50.00% Pervious = 0.104 ac 50.00% Impervious = 0.104 ac

SILV.01_RUNOFF_ANALYSIS_2.0

Type IA 24-hr 10 - Yr Rainfall=3.83"

Prepared by HydroCAD SAMPLER 1-800-927-7246 www.hydrocad.net

Printed 5/31/2020

HydroCAD® 10.10-3a Sampler s/n S24281 © 2020 HydroCAD Software Solutions LLC

Page 8

This report was prepared with the free HydroCAD SAMPLER, which is licensed for evaluation and educational use ONLY. For actual design or modeling applications you MUST use a full version of HydroCAD which may be purchased at www.hydrocad.net. Full programs also include complete technical support, training materials, and additional features which are essential for actual design work.

Summary for Subcatchment 5S: PARKING LOT EAST

Runoff = 0.05 cfs @ 9.11 hrs, Volume= 0.031 af, Depth= 3.60"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-30.00 hrs, dt= 0.01 hrs
Type IA 24-hr 10 - Yr Rainfall=3.83"

| Area (ac) | CN | Description |
|-----------|----|-------------------------|
| * 0.104 | 98 | |
| 0.104 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---------------|
| 100.0 | | | | | Direct Entry, |

Subcatchment 5S: PARKING LOT EAST

Hydrograph



SILV.01_RUNOFF_ANALYSIS_2.0

Type IA 24-hr 10 - Yr Rainfall=3.83"

Prepared by HydroCAD SAMPLER 1-800-927-7246 www.hydrocad.net

Printed 5/31/2020

HydroCAD® 10.10-3a Sampler s/n S24281 © 2020 HydroCAD Software Solutions LLC

Page 9

This report was prepared with the free HydroCAD SAMPLER, which is licensed for evaluation and educational use ONLY. For actual design or modeling applications you MUST use a full version of HydroCAD which may be purchased at www.hydrocad.net. Full programs also include complete technical support, training materials, and additional features which are essential for actual design work.

Summary for Subcatchment 8S: Pre-Development

Runoff = 0.03 cfs @ 8.01 hrs, Volume= 0.012 af, Depth= 1.34"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-30.00 hrs, dt= 0.01 hrs
Type IA 24-hr 10 - Yr Rainfall=3.83"

| Area (ac) | CN | Description |
|-----------|----|---------------------------------------|
| * 0.104 | 72 | Extg pervious, Pre-Lewis and Clark CN |
| 0.104 | | 100.00% Pervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---------------|
| 5.0 | | | | | Direct Entry, |

Subcatchment 8S: Pre-Development

Hydrograph



SILV.01_RUNOFF_ANALYSIS_2.0

Type IA 24-hr 10 - Yr Rainfall=3.83"

Prepared by HydroCAD SAMPLER 1-800-927-7246 www.hydrocad.net

Printed 5/31/2020

HydroCAD® 10.10-3a Sampler s/n S24281 © 2020 HydroCAD Software Solutions LLC

Page 10

This report was prepared with the free HydroCAD SAMPLER, which is licensed for evaluation and educational use ONLY. For actual design or modeling applications you MUST use a full version of HydroCAD which may be purchased at www.hydrocad.net. Full programs also include complete technical support, training materials, and additional features which are essential for actual design work.

Summary for Pond 4P: Pervious Pavement

Inflow Area = 0.104 ac, 100.00% Impervious, Inflow Depth = 3.60" for 10 - Yr event
Inflow = 0.05 cfs @ 9.11 hrs, Volume= 0.031 af
Outflow = 0.05 cfs @ 9.13 hrs, Volume= 0.031 af, Atten= 0%, Lag= 1.0 min
Discarded = 0.05 cfs @ 9.13 hrs, Volume= 0.031 af

Routing by Stor-Ind method, Time Span= 0.00-30.00 hrs, dt= 0.01 hrs
Peak Elev= -2.50' @ 9.13 hrs Surf.Area= 0.104 ac Storage= 0.000 af

Plug-Flow detention time= 1.7 min calculated for 0.031 af (100% of inflow)
Center-of-Mass det. time= 1.7 min (749.7 - 748.0)

| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|---|
| #1 | -2.50' | 0.062 af | 30.20'W x 150.00'L x 1.50'H Gravel Storage 0.156 af Overall x 40.0% Voids |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Discarded | -2.50' | 2.500 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.26 cfs @ 9.13 hrs HW=-2.50' (Free Discharge)
↳ **1=Exfiltration** (Exfiltration Controls 0.26 cfs)

SILV.01_RUNOFF_ANALYSIS_2.0

Type IA 24-hr 10 - Yr Rainfall=3.83"


Prepared by HydroCAD SAMPLER 1-800-927-7246 www.hydrocad.net
HydroCAD® 10.10-3a Sampler s/n S24281 © 2020 HydroCAD Software Solutions LLC

Printed 5/31/2020
Page 11

This report was prepared with the free HydroCAD SAMPLER, which is licensed for evaluation and educational use ONLY. For actual design or modeling applications you MUST use a full version of HydroCAD which may be purchased at www.hydrocad.net. Full programs also include complete technical support, training materials, and additional features which are essential for actual design work.

Pond 4P: Pervious Pavement

Hydrograph



SCI Directors and Staff

| | |
|-------------------------|---|
| Marc Schlossberg | SCI Co-Director, and Professor of Planning, Public Policy, and Management, University of Oregon |
| Nico Larco | SCI Co-Director, and Professor of Architecture, University of Oregon |
| Megan Banks | SCYP Director, University of Oregon |
| Sean Vermilya | Report Coordinator |
| Katie Fields | SCYP Graduate Employee |
| Danielle Lewis | Graphic Designer |